

LXHIOV 3.6/6kV Cable



Eland Product Group: MP05

APPLICATION

Portuguese Medium Voltage cable for power distribution and power supply stations used in Utility and Industrial applications, for rated voltages up to 3.6/6kV. Suitable for fixed installations, indoor or outdoor, in open air on cable trays, or underground in ducts or directly buried.

CHARACTERISTICS

Voltage Rating U_0/U (Um)
3.6/6 (7.2)kV

Test Voltage
12.6kV

Temperature Range
Fixed: -20°C to +90°C

Minimum Bending Radius
15 x overall diameter

CONSTRUCTION

Conductor
Class 2 Aluminium, circular, stranded

Conductor Screen
Semi-conductive XLPE (Cross-Linked Polyethylene)

Insulation
XLPE (Cross-Linked Polyethylene)

Insulation Screen
Semi-conductive XLPE (Cross-Linked Polyethylene)

Metallic Screen
Copper wire screen

Sheath
PVC (Polyvinyl Chloride)

Sheath Colour
● Black

STANDARDS

IEC 60228, IEC 60502-2

Flame Retardant according to BS EN/IEC 60332-1-2

ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab®, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.



DIMENSIONS

ELAND PART NO.	NO. OF CORES	CONDUCTOR NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER OVER INSULATION mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
MP0506K01025	1	25	12.5	20.0	505
MP0506K01035	1	35	13.5	21.0	560
MP0506K01050	1	50	15.0	22.0	615
MP0506K01070	1	70	16.5	24.0	705
MP0506K01095	1	95	18.0	25.5	830
MP0506K01120	1	120	20.0	27.5	950
MP0506K01150	1	150	21.0	29.0	1055
MP0506K01185	1	185	22.5	30.5	1205
MP0506K01240	1	240	25.5	33.5	1425
MP0506K01300	1	300	28.5	37.0	1695
MP0506K01400	1	400	32.0	40.0	2055
MP0506K01500	1	500	35.0	43.5	2450
MP0506K01600	1	630	40.0	49.0	3040
MP0506K03025	3	25	12.5	39.0	1935
MP0506K03035	3	35	13.5	41.5	2140
MP0506K03050	3	50	15.0	44.0	2395
MP0506K03070	3	70	16.5	48.0	2785
MP0506K03095	3	95	18.0	52.0	3270
MP0506K03120	3	120	20.0	56.0	3725
MP0506K03150	3	150	21.0	59.0	4170
MP0506K03185	3	185	22.5	62.5	4725
MP0506K03240	3	240	25.5	68.5	5750
MP0506K03300	3	300	28.5	76.0	6860
MP0506K03400	3	400	32.0	83.5	8390

ELECTRICAL CHARACTERISTICS

NO. OF CORES	CONDUCTOR NOMINAL CROSS SECTIONAL AREA mm ²	CONDUCTOR MAXIMUM SHORT CIRCUIT CURRENT T=1S kA	CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE μF/km	CURRENT CARRYING CAPACITY Amps	
						In Air	Buried
1	25	2.4	1.2000	0.41	0.27	121	124
1	35	3.3	0.8680	0.39	0.30	147	148
1	50	4.7	0.6410	0.37	0.33	176	175
1	70	6.6	0.4430	0.35	0.38	221	215
1	95	9.0	0.3200	0.33	0.42	270	258
1	120	11.3	0.2530	0.32	0.47	315	295
1	150	14.2	0.2060	0.31	0.51	357	331
1	185	17.5	0.1640	0.30	0.55	411	375
1	240	22.7	0.1250	0.29	0.60	489	436
1	300	28.3	0.1000	0.28	0.63	571	495
1	400	37.8	0.0778	0.28	0.66	670	567
1	500	47.2	0.0605	0.27	0.69	782	649
1	630	59.5	0.0469	0.26	0.79	925	746
3	25	2.4	1.2000	0.38	0.27	142	115
3	35	3.3	0.8680	0.36	0.30	170	136
3	50	4.7	0.6410	0.35	0.33	204	162
3	70	6.6	0.4430	0.32	0.38	253	198

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.



ELECTRICAL CHARACTERISTICS

NO. OF CORES	CONDUCTOR NOMINAL CROSS SECTIONAL AREA mm ²	CONDUCTOR MAXIMUM SHORT CIRCUIT CURRENT T=1S kA	CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE μF/km	CURRENT CARRYING CAPACITY Amps	
						In Air	Buried
3	95	9.0	0.3200	0.30	0.42	304	235
3	120	11.3	0.2530	0.29	0.47	351	268
3	150	14.2	0.2060	0.29	0.51	398	303
3	185	17.5	0.1640	0.28	0.55	455	343
3	240	22.7	0.1250	0.27	0.60	531	397
3	300	28.3	0.1000	0.26	0.63	606	448
3	400	37.8	0.0778	0.26	0.66	696	511