



8162 - LSF 300V Alternative Cable



Eland Product Group: A3B

APPLICATION

An overall foil and braid screen cable used over extended distances at high data rates for RS232 and RS422 applications

CHARACTERISTICS

Voltage Rating

300V

Temperature Rating

-20°C to +80°C

Minimum Bending Radius

10 x overall diameter

CONSTRUCTION

Conductor

Class 2 stranded tinned copper

Insulation

Gas Injection Foam PE (Polyethylene)

Collective Screen

Al/PET (Aluminium Foil/Polyester tape)

Drain Wire

Tinned copper

Braid

TCWB (Tinned Copper Wire Braid)

Sheath

PVC-LSF (Polyvinyl Chloride-Low Smoke Fume)

Core Identification

Pair 1: ● Black ● Red

Pair 2: ● Black ○ White

Sheath Colour

● Grey

Other colours available upon request

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/853/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].





DIMENSIONS

ELAND PART NO.	NO. OF PAIRS	AWG (NO. OF STRANDS)	NOMINAL DIAMETER OF STRANDS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A3B8162LSFGR	2	AWG24(7)	0.2	8.71	85

ELECTRICAL CHARACTERISTICS

VELOCITY OF PROPAGATION %	IMPEDANCE ohms	CAPACITANCE AT 1kHz pF/m	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km
78	100	41	<84.6

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.