



GM-FS Locknut



Eland Product Group: HUM

APPLICATION

A polyamide locknut suitable for use with our HSK-K Gland. Reinforced with glass fibre, this hexagonal counter locknut secures fixings on metric thread cable glands.

CHARACTERISTICS

Operating Temperature -40°C to +100°C

Colours ● Grey ● Black

Note Other colours on request

CONSTRUCTION

Gland Material Polyamide V0 according to UL 94

STANDARDS

UL94

THE CABLE LAB[®] AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability




REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab*.







DESCRIPTION

ELAND PART NO.	IG	H	₩ mm
HUMLECM12MNL**0	M 12 x 1.5	5	17
HUMLECM16MNL**0	M 16 x 1.5	5	22
HUMLECM20MNL**0	M 20 x 1.5	6	27
HUMLECM25MNL**0	M 25 x 1.5	6.5	32
HUMLECM32MNL**0	M 32 × 1.5	7	41
HUMLECM40MNL**0	M 40 × 1.5	7	50
*HUMLECM50MNL**0	M 50 × 1.5	8	60
HUMLECM63MNL**0	M 63 x 1.5	8	75

Eland Part No. shown above designate the colour (). For each colour substitute * for a colour code as listed below. e.g. HUMLECM12MNLGR0= Grey

Colour Codes

COLOUR	Black	Grey
CODE	ВК	GR

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.