

LXHIORV 3.6/6kV Cable



Eland Product Group: MP59

APPLICATION

Portuguese Medium Voltage cable for power distribution and power supply stations used in Utility and Industrial applications, with a rated voltage of 3.6/6kV. Suitable for fixed installations including directly buried. Good mechanical protection.

CHARACTERISTICS

Voltage Rating U_o/U (Um)
3.6/6 (7.2)kV

Temperature Rating

Conductor maximum operating temperature: 90°C
Maximum short-circuit temperature: 250°C

Minimum Bending Radius

During installation: 15 x overall diameter
After installation: 10 x overall diameter

CONSTRUCTION

Conductor

Class 2 Aluminium, circular, stranded conductor

Conductor Screen

Semi-conductive XLPE (Cross-Linked Polyethylene)

Insulation

XLPE (Cross-Linked Polyethylene)

Insulation Screen

Semi-conductive XLPE (Cross-Linked Polyethylene)

Metallic Screen

Copper wire screen

Tape

Plastic tape

Filler

Extruded polymeric material

Bedding

PVC (Polyvinyl Chloride)

Armour

SWA (Galvanized Steel Wire Armoured)

Sheath

PVC (Polyvinyl Chloride)

Sheath Colour

●Black

STANDARDS

IEC 60228, IEC 60502-2
Flame retardant to IEC 60332-1-2, IEC 60332-3-24,

ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab®, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



8578



FS 672069



EMS 672067



OHS 672066

REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.



KM 674287



DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP5906KV03025	3	25	12.5	44.0	3 320
MP5906KV03035	3	35	13.5	46.5	3 775
MP5906KV03050	3	50	15.0	49.5	4 340
MP5906KV03070	3	70	16.5	53.5	5 280
MP5906KV03095	3	95	18.0	57.5	6 325
MP5906KV03120	3	120	20.0	61.0	7 290
MP5906KV03150	3	150	21.0	64.5	8 300
MP5906KV03185	3	185	22.5	68.0	9 640
MP5906KV03240	3	240	25.5	74.5	11 985
MP5906KV03300	3	300	28.5	82.0	14 475

ELECTRICAL CHARACTERISTICS

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT, T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE µF/km
		In air	Buried				
3	25	111	115	2.4	1.2000	0.38	0.27
3	35	133	136	3.3	0.8680	0.36	0.30
3	50	159	162	4.7	0.6410	0.35	0.33
3	70	196	198	6.6	0.4430	0.32	0.38
3	95	238	236	9.0	0.3200	0.30	0.42
3	120	274	268	11.3	0.2530	0.29	0.47
3	150	309	302	14.2	0.2060	0.29	0.51
3	185	354	342	17.5	0.1640	0.28	0.55
3	240	415	395	22.7	0.1250	0.27	0.60
3	300	472	444	28.3	0.1000	0.26	0.63

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.