



DIMENSIONS 3.6/6kV

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP2306KV01025	1	25	12.5	25.5	810
MP2306KV01035	1	35	13.5	26.5	870
MP2306KV01050	1	50	15.0	27.5	940
MP2306KV01070	1	70	16.5	29.0	1050
MP2306KV01095	1	95	18.0	31.0	1180
MP2306KV01120	1	120	20.0	32.5	1315
MP2306KV01150	1	150	21.0	34.0	1450
MP2306KV01185	1	185	22.5	35.5	1605
MP2306KV01240	1	240	25.5	38.5	1875
MP2306KV01300	1	300	28.5	42.0	2190
MP2306KV01400	1	400	32.0	45.5	2595
MP2306KV01500	1	500	35.0	49.0	3035
MP2306KV01630	1	630	40.0	54.0	3690

ELECTRICAL CHARACTERISTICS 3.6/6kV

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT, T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE µF/km
		In air	Buried				
1	25	127	127	2.4	1.2000	0.44	0.27
1	35	153	151	3.3	0.8680	0.42	0.30
1	50	183	179	4.7	0.6410	0.40	0.33
1	70	229	219	6.6	0.4430	0.38	0.38
1	95	279	262	9.0	0.3200	0.36	0.42
1	120	324	299	11.3	0.2530	0.34	0.47
1	150	366	334	14.2	0.2060	0.33	0.51
1	185	420	377	17.5	0.1640	0.32	0.55
1	240	497	437	22.7	0.1250	0.32	0.60
1	300	575	493	28.3	0.1000	0.31	0.63
1	400	671	563	37.8	0.0778	0.30	0.66
1	500	779	641	47.2	0.0605	0.29	0.69
1	630	915	732	59.5	0.0469	0.28	0.79



DIMENSIONS 6/10kV

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP2310KV01025	1	25	14.5	27.5	900
MP2310KV01035	1	35	15.5	28.5	965
MP2310KV01050	1	50	17.0	29.5	1035
MP2310KV01070	1	70	18.5	31.0	1155
MP2310KV01095	1	95	20.0	33.0	1290
MP2310KV01120	1	120	22.0	34.5	1445
MP2310KV01150	1	150	23.0	36.0	1565
MP2310KV01185	1	185	24.5	37.5	1745
MP2310KV01240	1	240	27.0	40.0	1980
MP2310KV01300	1	300	30.0	43.0	2275
MP2310KV01400	1	400	32.5	46.0	2655
MP2310KV01500	1	500	35.5	49.0	3065
MP2310KV01630	1	630	40.5	54.5	3725

ELECTRICAL CHARACTERISTICS 6/10kV

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT. T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE µF/km
		In air	Buried				
1	25	129	127	2.4	1.2000	0.46	0.22
1	35	155	151	3.3	0.8680	0.44	0.24
1	50	185	179	4.7	0.6410	0.42	0.26
1	70	232	219	6.6	0.4430	0.39	0.30
1	95	282	262	9.0	0.3200	0.37	0.33
1	120	326	298	11.3	0.2530	0.36	0.37
1	150	369	333	14.2	0.2060	0.35	0.39
1	185	423	377	17.5	0.1640	0.34	0.43
1	240	498	436	22.7	0.1250	0.32	0.47
1	300	576	493	28.3	0.1000	0.31	0.53
1	400	672	564	37.8	0.0778	0.30	0.59
1	500	779	641	47.2	0.0605	0.29	0.65
1	630	915	732	59.5	0.0469	0.28	0.75



DIMENSIONS 8.7/15kV

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP2315KV01025	1	25	17.0	29.5	1005
MP2315KV01035	1	35	18.0	30.5	1075
MP2315KV01050	1	50	19.0	31.5	1150
MP2315KV01070	1	70	20.5	33.5	1270
MP2315KV01095	1	95	22.5	35.0	1430
MP2315KV01120	1	120	24.0	37.0	1575
MP2315KV01150	1	150	25.5	38.5	1720
MP2315KV01185	1	185	27.0	40.0	1885
MP2315KV01240	1	240	29.0	42.5	2150
MP2315KV01300	1	300	32.0	45.5	2455
MP2315KV01400	1	400	35.0	48.5	2850
MP2315KV01500	1	500	38.0	52.0	3300
MP2315KV01630	1	630	42.5	56.5	3950

ELECTRICAL CHARACTERISTICS 8.7/15kV

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT, T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE μF/km
		In air	Buried				
1	25	130	127	2.4	1.2000	0.48	0.18
1	35	157	151	3.3	0.8680	0.46	0.19
1	50	187	179	4.7	0.6410	0.43	0.21
1	70	234	219	6.6	0.4430	0.41	0.24
1	95	284	261	9.0	0.3200	0.39	0.27
1	120	329	298	11.3	0.2530	0.37	0.29
1	150	372	333	14.2	0.2060	0.36	0.31
1	185	425	376	17.5	0.1640	0.35	0.34
1	240	501	435	22.7	0.1250	0.34	0.37
1	300	579	493	28.3	0.1000	0.32	0.42
1	400	674	563	37.8	0.0778	0.31	0.46
1	500	790	641	47.2	0.0605	0.30	0.51
1	630	917	732	59.5	0.0469	0.29	0.58



DIMENSIONS 12/20kV

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP2320KV01035	1	35	20.0	32.5	1180
MP2320KV01050	1	50	21.0	34.0	1275
MP2320KV01070	1	70	22.5	35.5	1405
MP2320KV01095	1	95	24.5	37.5	1570
MP2320KV01120	1	120	26.0	39.0	1720
MP2320KV01150	1	150	27.5	40.5	1875
MP2320KV01185	1	185	29.0	42.0	2045
MP2320KV01240	1	240	31.0	44.5	2315
MP2320KV01300	1	300	34.0	47.5	2635
MP2320KV01400	1	400	37.0	51.0	3060
MP2320KV01500	1	500	40.0	54.0	3500
MP2320KV01630	1	630	44.5	59.0	4200

ELECTRICAL CHARACTERISTICS 2/20kV

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT. T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE µF/km
		In air	Buried				
1	35	158	151	3.3	0.8680	0.47	0.17
1	50	189	178	4.7	0.6410	0.45	0.18
1	70	235	219	6.6	0.4430	0.42	0.21
1	95	286	261	9.0	0.3200	0.40	0.23
1	120	330	297	11.3	0.2530	0.38	0.25
1	150	373	333	14.2	0.2060	0.37	0.27
1	185	426	376	17.5	0.1640	0.36	0.29
1	240	503	435	22.7	0.1250	0.35	0.32
1	300	581	493	28.3	0.1000	0.33	0.35
1	400	676	563	37.8	0.0778	0.32	0.39
1	500	783	641	47.2	0.0605	0.31	0.43
1	630	918	732	59.5	0.0469	0.30	0.49



DIMENSIONS 18/30kV

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP2330KV01050	1	50	26.0	39.0	1595
MP2330KV01070	1	70	27.5	41.0	1760
MP2330KV01095	1	95	29.5	42.5	1920
MP2330KV01120	1	120	31.0	44.5	2105
MP2330KV01150	1	150	32.5	46.0	2250
MP2330KV01185	1	185	34.0	47.5	2460
MP2330KV01240	1	240	36.0	50.0	2780
MP2330KV01300	1	300	39.0	53.5	3125
MP2330KV01400	1	400	42.0	56.5	3585
MP2330KV01500	1	500	45.0	59.5	4020
MP2330KV01630	1	630	49.5	64.5	4765

ELECTRICAL CHARACTERISTICS 18/30kV

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT. T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE μF/km
		In air	Buried				
1	50	191	178	4.7	0.641	0.48	0.14
1	70	238	218	6.6	0.443	0.45	0.16
1	95	288	260	9.0	0.320	0.43	0.17
1	120	333	297	11.3	0.253	0.41	0.19
1	150	376	332	14.2	0.206	0.40	0.20
1	185	430	375	17.5	0.164	0.39	0.21
1	240	506	435	22.7	0.125	0.37	0.24
1	300	584	493	28.3	0.100	0.36	0.26
1	400	679	563	37.8	0.0778	0.34	0.29
1	500	786	642	47.2	0.0605	0.33	0.31
1	630	920	734	59.5	0.0469	0.32	0.35

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.