

Belden 8772 Multi-Conductor Audio, Control and Instrumentation Cable



Eland Product Group: A4B

APPLICATION

A multi-core cable for audio, control and instrumentation applications.

CHARACTERISTICS

Voltage Rating
300V

Temperature Rating
-20°C to +60°C

Minimum Bending Radius
10 x overall diameter

CONSTRUCTION

Conductor
Class 2 stranded tinned copper

Insulation
PE (Polyethylene)

Screen
Beldfoil[®] (Aluminium foil polyester tape)

Drain Wire
Tinned copper

Sheath
PVC (Polyvinyl Chloride)

Core Identification
● Black ● Red ● Transparent

Sheath Colour
● Grey

STANDARDS

Belden 8772, UL Style 2093

Vertical tray fire propagation and smoke release test:
UL 1685 FT1

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECCE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].





DIMENSIONS

| ELAND PART NO. | BELDEN REFERENCE | NO. OF PAIRS | AWG (NO. OF STRANDS) | NOMINAL DIAMETER OF STRANDS mm | NOMINAL OVERALL DIAMETER mm | NOMINAL WEIGHT kg/km |
|----------------|---------------------|-----------------|-------------------------|--------------------------------------|-----------------------------------|----------------------------|
| A4B8772 | 8772 | 3 | AWG20(7) | 0.3 | 5.53 | 43.15 |

ELECTRICAL CHARACTERISTICS

| AWG (NO. OF STRANDS) | CAPACITANCE pF/m | | MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km |
|-------------------------|------------------------|---------------------|---|
| | Conductor to Conductor | Conductor to Shield | |
| AWG20(7) | 88.58 | 167.33 | 32.81 |

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.