



Click here for more information:
elandcables.com | [FLYW Cable](#)

ELAND[®]
CABLES

FLYW Cable



Eland Product Group: A2A

APPLICATION

FLYW Cables are PVC insulated single-core unshielded low-tension wires used in the automotive industry. Offers resistance against oils, fuels, acids and lyes. Heat Resistant and Hot Pressure Resistant.

CHARACTERISTICS

Temperature Rating
-40°C to +125°C

CONSTRUCTION

Conductor
Cu-ETP1 Bare Copper

Insulation
PVC (Polyvinyl Chloride)

Sheath Colour
● Red

STANDARDS

ISO 6722 Class C

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECCE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].





DIMENSIONS

ELAND PART NUMBER	NUMBER OF CORES	NOMINAL CROSS- SECTIONAL AREA mm ²	NOMINAL NO. AND DIAMETER WIRES No/mm	MAXIMUM CONDUCTOR DIAMETER mm	NOMINAL ELECTRICAL RESISTANCE AT 20°C MAX mΩ/m	NOMINAL THICKNESS INSULATION WALL mm	NOMINAL OVERALL DIAMETER (MIN) mm	NOMINAL OVERALL DIAMETER (MAX) mm	NOMINAL WEIGHT kg/km
A2AT00200005**	1	0.50	16/0.20	1.00	37.10	0.48	2.00	2.30	8
A2AT00200075**	1	0.75	24/0.20	1.20	24.70	0.48	2.20	2.50	11
A2AT0020010**	1	1.00	32/0.20	1.35	18.50	0.48	2.40	2.70	15
A2AT0020015**	1	1.50	30/0.25	1.70	12.70	0.48	2.70	3.00	20
A2AT0020020**	1	2.50	50/0.25	2.20	7.60	0.56	3.30	3.60	32
A2AT0020040**	1	4.00	56/0.31	2.75	4.71	0.64	4.00	4.40	48
A2AT0020060**	1	6.00	84/0.31	3.30	3.14	0.64	4.60	5.00	68
A2AT002010**	1	10.00	80/0.40	4.50	1.82	0.80	6.00	6.50	117
A2AT002016**	1	16.00	126/0.40	5.20	1.16	0.80	8.00	8.30	193
A2AT002025**	1	25.00	196/0.40	6.50	0.70	1.04	10.10	10.40	274
A2AT002035**	1	35.00	276/0.40	7.70	0.50	1.04	11.30	11.60	397
A2AT002050**	1	50.00	396/0.40	9.20	0.30	1.20	13.20	13.50	547
A2AT002070**	1	70.00	556/0.40	11.00	0.20	1.20	15.20	15.50	769
A2AT002095**	1	95.00	741/0.40	14.80	0.20	1.28	17.00	18.00	990

COLOUR	Red	Black	Blue	Yellow	Grey	Brown	White	Violet	Green	Natural				
CODE	RD	BK	BL	YW	GR	BR	WH	VI	GN	NT				