

# 8471 600V LSZH Alternative Cable



ELAND CABLES ©

Eland Product Group: A3B

## APPLICATION

8471 Alternative cable is suitable for use in instrumentation, security, data and audio applications where protection against electrical interference is not required. For installations where fire, smoke emission and toxic fumes create a potential risk to life and equipment.

## CHARACTERISTICS

**Voltage Rating**  
600V

**Temperature Rating**  
Fixed: -40°C to +70°C

## CONSTRUCTION

**Conductor**  
Stranded tinned copper conductor

**Insulation**  
HDPE (High-Density Polyethylene)

**Sheath**  
LSZH (Low Smoke Zero Halogen)

**Core Identification**  
Pair 1: ● Black ○ White

**Sheath Colour**  
● Violet

## DIMENSIONS

ELAND PART NO.	NO. OF PAIRS	AWG (NO. OF STRANDS)	NOMINAL DIAMETER OF STRANDS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A3B8471NH600V	1	AWG16(19)	0.3	6.95	54

## ELECTRICAL CHARACTERISTICS

MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C  
ohms/km

15.2

## THE CABLE LAB®

### AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



## SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: [www.elandcables.com/company/about-us/esg-sustainability](http://www.elandcables.com/company/about-us/esg-sustainability)



## REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab®.

