

Two Part Cable Cleats



Eland Product Group: FCG

APPLICATION

Designed to support and retain your cables within your cable tray system. Easily stackable to save space.

CONSTRUCTION

Polypropylene. Made of non-flame propagating material.

CHARACTERISTICS


Temperature Rating

Constant: 80°C Intermittent: 95°C

Colour

Black

DIMENSIONS



THE CABLE LAB®

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.





SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability





SCIENCE BASED AMBITION FOR 1.5°C AMBITION FOR 1.5°C







REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab®.





ELAND PART NO.	NOMINAL OVERALL DIAMETER		Α	В	С	BOLT HOLES	PACK QUANTITY
	mm	inches	mm	mm	mm	mm	
TCC10	57 - 63.5	2.25 - 2.5	60	77	76.2	2 x 10	1
TCC11 CLEAT	63.4 - 69.8	2.5 - 2.75	63.5	86	114.3	2 x 10	1
TCC12	69.7 - 76.2	2.75 - 3	63.5	93	114.3	2 x 10	
TCC14	76.1 - 82.5	3 - 3.25	63.5	98.5	114.3	2 x 10	

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.