



Click here for more information:
elandcables.com | [FLR5Y-A Cable](#)

**ELAND[®]
CABLES**

FLR5Y-A Cable



Eland Product Group:

APPLICATION

The FLR5Y-A Cable is a PTFE insulated low-tension automotive wire used in motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits. Offers excellent resistance to oils, fuels, breaking fluids, acids, lyes and organic media. Heat resistant.

CHARACTERISTICS

Temperature Rating

-40°C to +260°C

CONSTRUCTION

Conductor

Silver Plated Copper (Type A)

Insulation

PTFE (Polytetrafluoroethylene)

Sheath Colour

● Blue

STANDARDS

ISO 6722 Class H

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECCE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].



DIMENSIONS

ELAND PART NUMBER	NUMBER OF CORES	NOMINAL CROSS-SECTION	NOMINAL NO. AND DIAMETER OF WIRES	MAXIMUM DIAMETER OF CONDUCTOR	NOMINAL ELECTRICAL RESISTANCE AT 20°C MAX	NOMINAL INSULATION THICKNESS	NOMINAL OVERALL DIAMETER (MIN)	NOMINAL OVERALL DIAMETER (MAX)	NOMINAL WEIGHT
		mm	No/mm	mm	mΩ/m	mm	mm	mm	kg/km
A2AT016000022**	1	0.22	7/0.21	0.7	87.9	0.20	1.1	1.2	3
A2AT016000035**	1	0.35	7/0.27	0.8	56.8	0.20	1.25	1.35	5
A2AT01600005**	1	0.5	19/0.19	1.0	38.6	0.22	1.4	1.6	6
A2AT01600075**	1	0.75	19/0.24	1.2	25.7	0.24	1.7	1.9	10
A2AT0160010**	1	1.00	19/0.27	1.35	19.3	0.24	1.75	1.95	11
A2AT0160015**	1	1.5	19/0.33	1.7	13.2	0.24	2.1	2.3	17
A2AT0160025**	1	2.5	19/0.41	2.2	7.92	0.28	2.5	2.8	25