

Wraparound Cable Cleat



Eland Product Group: **FCG**

APPLICATION

Designed to fix, retain and support cables. Single fixing provides a simple but strong means of securing cables.

CONSTRUCTION

Material

UV resistant polypropylene. Made of non-flame propagating black polypropylene

CHARACTERISTICS

Temperature Rating

Constant: 80°C

Intermittent: 95°C

Colour

● Black

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



SCIENCE
BASED
TARGETS

**BUSINESS
AMBITION FOR 1.5°C**




REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].



DIMENSIONS



ELAND PART NO.	MAXIMUM DIAMETER OF CABLE		A mm	B mm	BOLT HOLES mm	PACK QUANTITY
	mm	inches				
NYLON CLEAT CC5	12.7	0.5	30	16	6	100
NYLON CLEAT CC6	15.2	0.6	32	17	6	100
NYLON CLEAT CC7	17.8	0.7	35	21	6	100
NYLON CLEAT CC8	20.3	0.8	37	24	6	100
NYLON CLEAT CC9	22.8	0.9	40	26	6	100
NYLON CLEAT CC10	25.4	1	43	29	6	100
NYLON CLEAT CC11	27.7	1.1	48	33	6	100
NYLON CLEAT CC12	30.5	1.2	56	36	10	50
NYLON CLEAT CC14	35.5	1.4	62	41	10	50
NYLON CLEAT CC16	40.6	1.6	67	47	10	50
NYLON CLEAT CC18	45.7	1.8	71	52	10	50
NYLON CLEAT CC20	50.8	2	77	56	10	50

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.