



Click here for more information:  
[elandcables.com](http://elandcables.com) | [MMO/J HF Cable](#)

**ELAND<sup>®</sup>**  
**CABLES**

## MMO/J HF Cable



Eland Product Group: B1U

### APPLICATION

This cable is suitable for fixed installations, indoor, outdoor, on surface and in conduits. Not to be laid in soil nor directly in cast concrete. Where needed halogen free, non corrosive gases and low smoke density cables. Self extinguishing, no after-burning.

### CHARACTERISTICS

**Voltage Rating** Uo/U  
450/750V

**Temperature Rating**  
Operating: -15°C to +70°C

**Short Circuit Temperature**  
160°C

**Minimum Bending Radius**  
9 x overall diameter

### CONSTRUCTION

**Conductor**  
Circular solid copper

**Insulation**  
Halogen free polyolefine

**Filler**  
Halogen free filling

**Sheath**  
Halogen free polyolefine, UV resistant

#### Core identification

##### MMO

● Black numbered

##### MMJ

3 core: ● Green/Yellow ● Blue ● Brown

5 core: ● Green/Yellow ● Blue ● Brown ● Black ● Grey

**Sheath Colour**  
○ White

### STANDARDS

HD 308 S2, EN 60754-2, EN 61034-2

Flame retardant according to EN 60332-3-23

#### THE CABLE LAB<sup>®</sup>

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



### SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: [www.elandcables.com/company/about-us/esg-sustainability](http://www.elandcables.com/company/about-us/esg-sustainability)



### REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab<sup>®</sup>.





## DIMENSIONS

### MM-O

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	NOMINAL OVERALL DIAMETER mm	MAXIMUM ALLOWED PULLING FORCE kN	NOMINAL WEIGHT kg/km
B1U070015WH	7	1.5	14	0.53	250
B1U070025WH	7	2.5	16	0.88	370
B1U120015WH	12	1.5	18	0.9	400
B1U120025WH	12	2.5	20	1.5	560
B1U190015WH	19	1.5	20	1.43	580
B1U190025WH	19	2.5	25	2.38	840
B1U270015WH	27	1.5	25	2.03	820
B1U270025WH	27	2.5	29	3.38	1190

### MM-J

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	NOMINAL OVERALL DIAMETER mm	MAXIMUM ALLOWED PULLING FORCE kN	NOMINAL WEIGHT kg/km
B1U030015WH	3	1.5	11	0.23	160
B1U030025WH	3	2.5	12	0.38	210
B1U030060WH	3	6	16	0.9	410
B1U03010WH	3	10	20	1.5	610
B1U050015WH	5	1.5	13	0.38	210
B1U050025WH	5	2.5	15	0.63	300
B1U050060WH	5	6	19	1.5	600
B1U04010WH	5	10	23	2.5	910
B1U05016WH	5	16	26	4	1270

## ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km
1.5	12.1
2.5	7.41
6	3.08
10	1.83
16	1.15

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.