



XHIOE(be) 18/30kV Cable



Eland Product Group: MP07

APPLICATION

Portuguese referenced Medium Voltage cable with additional waterblocking for power distribution and power supply stations used in Utility and Industrial applications, for rated voltages up to 18/30kV. Suitable for fixed installations, indoor or outdoor, in open air on cable trays, or underground in ducts or directly buried.

CHARACTERISTICS

Voltage Rating U₀/U (Um)
18/30 (36)kV

Test Voltage
63kV

Temperature Range
Fixed: -20°C to +90°C

Minimum Bending Radius
15 x overall diameter

CONSTRUCTION

Conductor
Stranded copper conductor

Conductor Screen
Semi-conductive XLPE (Cross-Linked Polyethylene)

Insulation
XLPE (Cross-Linked Polyethylene)

Insulation Screen
Semi-conductive XLPE (Cross-Linked Polyethylene) and tape

Metallic Screen
Copper wires

Tape
Waterblocking yarn

Outer Sheath
PE (Polyethylene)

Sheath Colour
● Black

STANDARDS

IEC 60228, IEC 60502-2

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECCE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].





DIMENSIONS

ELAND PART NO.	NO. OF CORES	CONDUCTOR NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER OVER INSULATION mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
MP0730K01050	1	50	26.0	34.5	1445
MP0730K01070	1	70	28.0	36.0	1695
MP0730K01095	1	95	29.5	38.0	2015
MP0730K01120	1	120	31.5	39.5	2300
MP0730K01150	1	150	32.5	41.0	2600
MP0730K01185	1	185	33.5	42.0	2985
MP0730K01240	1	240	36.5	45.0	3620
MP0730K01300	1	300	39.0	48.0	4315
MP0730K01400	1	400	42.0	51.0	5305
MP0730K01500	1	500	45.0	54.5	6310
MP0730K01630	1	630	51.0	58.0	8010
MP0730K03050	3	50	26.0	70.5	5800
MP0730K03070	3	70	28.0	74.5	6795
MP0730K03095	3	95	29.5	78.5	7985
MP0730K03120	3	120	31.5	82.5	9060
MP0730K03150	3	150	32.5	85.0	10030
MP0730K03185	3	185	33.5	88.0	11475
MP0730K03240	3	240	36.5	94.0	13630
MP0730K03300	3	300	39.0	100.0	16145
MP0730K03400	3	400	42.0	107.0	19650

ELECTRICAL CHARACTERISTICS

NO. OF CORES	CONDUCTOR NOMINAL CROSS SECTIONAL AREA mm ²	CONDUCTOR MAXIMUM SHORT CIRCUIT CURRENT T=1S kA	CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE µF/km	CURRENT CARRYING CAPACITY Amps	
						In Air	Buried
1	50	7.5	0.3870	0.42	0.21	236	226
1	70	10.0	0.2680	0.40	0.24	295	277
1	95	13.6	0.1930	0.38	0.27	359	333
1	120	17.2	0.1530	0.36	0.29	416	379
1	150	21.5	0.1240	0.35	0.31	471	425
1	185	26.5	0.0991	0.34	0.33	537	479
1	240	34.3	0.0754	0.33	0.38	639	558
1	300	42.9	0.0601	0.32	0.42	738	632
1	400	57.2	0.0470	0.30	0.46	858	720
1	500	71.5	0.0366	0.29	0.51	993	817
1	630	90.1	0.0283	0.29	0.56	1 143	922
3	50	7.5	0.3870	0.41	0.19	204	209
3	70	10.0	0.2680	0.37	0.21	253	256
3	95	13.6	0.1930	0.36	0.23	304	303
3	120	17.2	0.1530	0.34	0.25	351	345
3	150	21.5	0.1240	0.27	0.31	398	390
3	185	26.5	0.0991	0.28	0.33	455	440
3	240	34.3	0.0754	0.32	0.38	531	507
3	300	42.9	0.0601	0.35	0.42	606	571
3	400	57.2	0.0470	0.39	0.46	696	645

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.