



XHI1RV 12/20kV Cable



Eland Product Group: MP25

APPLICATION

Portuguese Medium voltage cable for power distribution and power supply stations used in Utility and Industrial applications, for rated voltages up to 12/20kV. Suitable for fixed installations, directly buried. Good mechanical protection.

CHARACTERISTICS

Voltage Rating U_o/U (U_m)
12/20 (24)kV

Temperature Rating

Conductor maximum operating temperature: 90°C
Maximum short-circuit temperature: 250°C

Minimum Bending Radius

During installation: 20 x overall diameter
After installation: 15 x overall diameter

CONSTRUCTION

Conductor

Class 2 stranded Copper

Conductor Screen

Semi-conductive XLPE (Cross-Linked Polyethylene)

Insulation

XLPE (Cross-Linked Polyethylene)

Insulation Screen

Semi-conductive XLPE (Cross-Linked Polyethylene)

Metallic Screen

Copper tape screen

Inner Sheath

Extruded PVC (Polyvinyl Chloride)

Armour

AWA - Aluminium wires, helically applied, tightened with plastic tapes

Sheath

Extruded PVC (Polyvinyl Chloride)

Sheath Colour

● Black

STANDARDS

IEC 60228, IEC 60502-2

ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab®, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



8578



FS 672069



EMS 672067



OHS 672066

REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.



RoHS 672067





DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP2520KV01035	1	35	20.0	32.5	1390
MP2520KV01050	1	50	21.0	34.0	1565
MP2520KV01070	1	70	23.0	35.5	1825
MP2520KV01095	1	95	24.5	37.5	2150
MP2520KV01120	1	120	26.5	39.5	2445
MP2520KV01150	1	150	27.5	40.5	2750
MP2520KV01185	1	185	28.5	42.0	3140
MP2520KV01240	1	240	31.5	45.0	3780
MP2520KV01300	1	300	34.0	47.5	4490
MP2520KV01400	1	400	37.0	51.0	5515
MP2520KV01500	1	500	40.0	54.5	6535
MP2520KV01630	1	630	46.0	58.0	8300

ELECTRICAL CHARACTERISTICS

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT, T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE μF/km
		In air	Buried				
1	35	204	195	5.0	0.5240	0.47	0.17
1	50	244	231	7.2	0.3870	0.44	0.19
1	70	304	282	10.0	0.2680	0.42	0.21
1	95	368	337	13.6	0.1930	0.40	0.23
1	120	425	383	17.2	0.1530	0.38	0.25
1	150	479	427	21.5	0.1240	0.37	0.27
1	185	544	479	26.5	0.0991	0.36	0.28
1	240	643	555	34.3	0.0754	0.35	0.32
1	300	739	626	42.9	0.0601	0.33	0.35
1	400	853	709	57.2	0.0470	0.32	0.39
1	500	979	799	71.5	0.0366	0.31	0.43
1	630	1 119	896	90.1	0.0283	0.30	0.47

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.