

ELAND[®] CABLES

FLYCY Cable



ELAND CABLES @

Eland Product Group: F02

APPLICATION

FLYCY are used as airfield lighting equipment primary cables for the series circuit connecting the Constant Current Regulators and the isolating transformers, and between the isolating transformers. Impact and Weather resistant.

CHARACTERISTICS

Rated Voltage Uo/U (Um) 1/2kV, 1.5/3kV, 2.5/5kV, 3/6kV, 5/10kV

Temperature Rating Fixed: -40°C to +90°C

Minimum Bending Radius 15 x Overall Diameter

CONSTRUCTION

Conductor Solid or stranded bare copper conductor

Insulation PVC (Polyvinyl chloride)

Optional Separator Separator tape

Shield

Concentric layer of bare copper wires, counter helix of copper tape

Outer Sheath

PVC (Polyvinyl chloride) - UV & Oll resistant

Sheath Colour

Red

DIMENSIONS

STANDARDS

ENV 50213, IEC 50602-2, VDE 0271

THE CABLE LAB[®] AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab*.



ELAND PART NO.	VOLTAGE kV	NUMBER OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL SHEATH THICKNESS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
F0202KV010060RD	1/2kV	1	6	1.4	10.0	170
F0203KV010060RD	1.5/3kV	1	6	1.4	12.5	240
F0205KV010060RD	2.5/5kV	1	6	1.4	13.0	250
F0206KV010060RD	3/6kV	1	6	1.4	13.0	250
F0206KV010160RD	3/6kV	1	16	1.4	15.0	465
F0210KV010060RD	5/10kV	1	6	1.4	16.5	360
F0210KV010100RD	5/10kV	1	10	1.4	17.0	390