

ELAND[®] CABLES

FLU6Y Cable



FLAND GARLES G

Eland Product Group:

APPLICATION

The FLU6Y cable is an FEP insulated low-tension automotive cable with ultra-low thickness insulation used in cable harnesses and motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits. Offers heat and cold resistance as well as excellent resistance to oils, fuels, breaking fluids, acids, lyes and organic media.

CHARACTERISTICS

Temperature Rating

-40°C to +200°C

CONSTRUCTION

Conductor

Plain, tinned silver- or Nickel-plated copper

Insulation FEP (Tetrafluoroethylene hexafluoropropylene)

Sheath Colour

● Red ● Black ● Blue ● Yellow ● Grey ● Brown ○ White ● Violet ● Green ◎ Natural

STANDARDS

ISO 6722 Class F

THE CABLE LAB®

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].

**** * RoHS* * * **

_		_			
	IN /		NIC	\square	NS
	V		UV U	IU.	UND -

DIVIENSIONS				_									
	ND PART JMBER		NUMBER OF CORES	CR0 SEC		NOMINAL NO.AND DIAMETER OF WIRES	MAXIMU DIAMETE OF CONDUCT	ER E	NOMINAL LECTRICAL ESISTANCE AT 20°C MAX	NOMINAL INSULATION THICKNESS	NOMINAL OVERALL DIAMETER (MIN)	NOMINAL OVERALL DIAMETER (MAX)	NOMINAL WEIGHT
				m	1m ²	No/mm	mm		mΩ/m	mm	mm	mm	kg/km
A2AT02	A2AT020000013**		1	0.	13	7/0.16	0.5		140	0.16	0.85	0.95	2.3
A2AT020000014**		1	0.	14	7/0.16	0.5		140	0.16	0.85	0.95	2.3	
A2AT020000022**		1	0.	22	7/0.21	0.7		86.5	0.16	0.95	1.05	2.9	
A2AT020000035**		1	0.	35	7/0.26	0.7		55.5	0.16	1.10	1.20	4.3	
A2AT02000005**		1	0.	50	19/0.19	1.0		38.2	0.16	1.30	1.40	6.4	
A2AT02000075**		1	0.	75	19/0.23	1.2		25.4	0.16	1.50	1.60	8.8	
A2AT0200010**		1	1.	00	19/0.26	1.4		19.1	0.16	1.65	1.75	10.8	
A2AT0200015**		1	1.	50	19/0.32	1.7		13.0	0.16	1.90	2.10	15.8	
A2AT02	A2AT0200025**		1	2.	50	19/0.41	2.2		7.82	0.20	2.45	2.75	25.8
COLOUR F	Red	Black	Blue	Yellow	Grey	Brown	White	Viole	t Green	Natural			
UCLOUR I	i tou	BIGOR	Dide	Tenow	arey	DIOWI	vviille	VIOLE	L Shoon	ivaluiai			
CODE	RD	BK	BL	YW	GR	BR	WH	VI	GN	NT			