

FLRY A Cable



Eland Product Group: A2A

APPLICATION

Low-tension electric wire for Automobiles. Used in Motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits. Flame retardant. Highly resistant against acids, lyes, Petrol and diesel. Flexible conductors with thin wall insulation.

CHARACTERISTICS

Test Voltage

3kv i.e < 0.5mm²

5kv i.e > 0.5mm²

Temperature Rating

Fixed: -40°C to +105°C

CONSTRUCTION

Conductor

Flexible copper conductor, plain or tinned (concentric lay)

Insulation

PVC (Polyvinyl Chloride) (thin wall)

Sheath Colour

● Black ● Blue ● Orange ● Red ○ White

Other colours available upon request

STANDARDS

DIN 72551-6, BMW GS 95007-1, Ford WSK 1A2348-A2, FIAT 91107/13

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].





DIMENSIONS

ELAND PART NO.	NOMINAL CROSS SECTIONAL AREA mm ²	NO. OF STRANDS	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A2AFLRYA00022**	0.22	7	1.2	3.2
A2AFLRYA00035**	0.35	7	1.3	4.4
A2AFLRYA00005**	0.5	19	1.6	6.3
A2AFLRYA00075**	0.75	19	1.9	9.3
A2AFLRYA0010**	1	19	2.1	11.8
A2AFLRYA0015**	1.5	19	2.4	16.8
A2AFLRYA0020**	2	19	2.6	21.9
A2AFLRYA0025**	2.5	19	3	26.2

** *Eland Part No. shown above designate the sheath colour (*). For each colour substitute * for a colour code as listed below. e.g. A2AFLRYA00022WH = 0.22mm² White

DIMENSIONS

NOMINAL CROSS SECTIONAL AREA mm ²	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km	CURRENT CARRYING CAPACITY amps
0.22	84.8	5
0.35	52.0	9
0.5	37.1	12
0.75	24.7	16
1	18.5	19
1.5	12.7	22
2	9.42	25
2.5	7.6	30

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.