



Click here for more information:
elandcables.com | [LXHIAV Cable](#)

ELAND[®]
CABLES

LXHIAV Cable



Eland Product Group: MP48

APPLICATION

Portuguese Medium Voltage cable for power distribution and power supply stations used in Utility and Industrial applications, with a rated voltage of 3.6/6kV to 18/30kV. Suitable for fixed installations including directly buried. Good mechanical protection.

CHARACTERISTICS

Voltage Rating U_o/U (Um)

3.6/6 (7.2)kV,
6/10 (12)kV,
8.7/15 (17.5)kV,
12/20 (24)kV,
18/30 (36)kV

Temperature Rating

Conductor maximum operating temperature: 90°C
Maximum short-circuit temperature: 250°C

Minimum Bending Radius

During installation: 15 x overall diameter
After installation: 10 x overall diameter

CONSTRUCTION

Conductor

Class 2 Aluminium, circular, stranded

Conductor Screen

Semi-conductive XLPE (Cross-Linked Polyethylene)

Insulation

XLPE (Cross-Linked Polyethylene)

Insulation Screen

Semi-conductive XLPE (Cross-Linked Polyethylene)

Metallic Screen

Copper tape screen

Filler

Extruded polymeric material

Bedding

PVC (Polyvinyl Chloride)

Armour

STA (Steel Tape Armoured)

Sheath

PVC (Polyvinyl Chloride)

Sheath Colour

● Black

STANDARDS

IEC 60502-2, IEC 60228

Flame retardant according to EN/IEC 60332-1-2,
EN/IEC 60332-3-24,

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].





DIMENSIONS 3.6/6kV

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP4806KV03025	3	25	12.5	44.0	2860
MP4806KV03035	3	35	13.5	46.5	3140
MP4806KV03050	3	50	15.0	49.5	3460
MP4806KV03070	3	70	16.5	53.5	3965
MP4806KV03095	3	95	18.0	57.5	4575
MP4806KV03120	3	120	20.0	61.0	5095
MP4806KV03150	3	150	21.0	64.5	5650
MP4806KV03185	3	185	22.5	68.0	6320
MP4806KV03240	3	240	25.5	74.5	7545
MP4806KV03300	3	300	28.5	82.0	8845
MP4806KV03400	3	400	32.0	91.0	11485

ELECTRICAL CHARACTERISTICS 3.6/6kV

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT, T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE µF/km
		In air	Buried				
3	25	111	115	2.4	1.2000	0.38	0.27
3	35	133	136	3.3	0.8680	0.36	0.30
3	50	159	162	4.7	0.6410	0.35	0.33
3	70	196	198	6.6	0.4430	0.32	0.38
3	95	238	236	9.0	0.3200	0.30	0.42
3	120	274	268	11.3	0.2530	0.29	0.47
3	150	309	302	14.2	0.2060	0.29	0.51
3	185	354	342	17.5	0.1640	0.28	0.55
3	240	415	395	22.7	0.1250	0.27	0.60
3	300	472	444	28.3	0.1000	0.26	0.63
3	400	545	504	37.8	0.0778	0.26	0.66

DIMENSIONS 6/10kV

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP4810KV03025	3	25	14.5	49.0	3310
MP4810KV03035	3	35	15.5	51.5	3620
MP4810KV03050	3	50	17.0	54.0	3460
MP4810KV03070	3	70	18.5	58.0	4500
MP4810KV03095	3	95	20.0	62.0	5075
MP4810KV03120	3	120	22.0	66.0	5690
MP4810KV03150	3	150	23.0	69.5	6305
MP4810KV03185	3	185	24.5	72.5	6975
MP4810KV03240	3	240	27.0	78.0	8015
MP4810KV03300	3	300	30.0	85.0	9305
MP4810KV03400	3	400	32.5	93.0	11775



ELECTRICAL CHARACTERISTICS 6/10kV

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT. T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE µF/km
		In air	Buried				
3	25	111	115	2.4	1.2000	0.40	0.22
3	35	133	136	3.3	0.8680	0.39	0.24
3	50	159	162	4.7	0.6410	0.37	0.26
3	70	196	198	6.6	0.4430	0.34	0.30
3	95	238	236	9.0	0.3200	0.32	0.33
3	120	274	268	11.3	0.2530	0.31	0.37
3	150	309	302	14.2	0.2060	0.30	0.39
3	185	354	342	17.5	0.1640	0.29	0.43
3	240	415	395	22.7	0.1250	0.28	0.47
3	300	472	444	28.3	0.1000	0.27	0.53
3	400	545	504	37.8	0.0778	0.26	0.59

DIMENSIONS 8.7/15kV

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP4815KV03025	3	25	17.0	54.5	3870
MP4815KV03035	3	35	18.0	57.0	4200
MP4815KV03050	3	50	19.0	59.0	4530
MP4815KV03070	3	70	20.5	63.5	5100
MP4815KV03095	3	95	22.5	67.0	5750
MP4815KV03120	3	120	24.0	71.5	6405
MP4815KV03150	3	150	25.5	74.5	7075
MP4815KV03185	3	185	27.0	77.5	7670
MP4815KV03240	3	240	29.0	83.5	8845
MP4815KV03300	3	300	32.0	91.5	11075
MP4815KV03400	3	400	35.0	98.5	12785

ELECTRICAL CHARACTERISTICS 8.7/15kV

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT. T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE µF/km
		In air	Buried				
3	25	111	115	2.4	1.2000	0.43	0.18
3	35	133	136	3.3	0.8680	0.41	0.19
3	50	159	162	4.7	0.6410	0.39	0.21
3	70	196	198	6.6	0.4430	0.36	0.24
3	95	238	236	9.0	0.3200	0.34	0.27
3	120	274	268	11.3	0.2530	0.33	0.29
3	150	309	302	14.2	0.2060	0.32	0.31
3	185	354	342	17.5	0.1640	0.31	0.34
3	240	415	395	22.7	0.1250	0.30	0.37
3	300	472	444	28.3	0.1000	0.29	0.42
3	400	545	504	37.8	0.0778	0.27	0.46



DIMENSIONS 12/20kV

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP4820KV03035	3	35	20.0	61.0	4685
MP4820KV03050	3	50	21.0	64.0	5110
MP4820KV03070	3	70	22.5	68.0	5710
MP4820KV03095	3	95	24.5	72.0	6435
MP4820KV03120	3	120	26.0	76.0	7080
MP4820KV03150	3	150	27.5	79.0	7680
MP4820KV03185	3	185	29.0	82.5	8445
MP4820KV03240	3	240	31.0	89.5	10535
MP4820KV03300	3	300	34.0	96.5	11970
MP4820KV03400	3	400	37.0	103.0	13370

ELECTRICAL CHARACTERISTICS 12/20kV

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT, T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE μF/km
		In air	Buried				
3	35	133	136	3.3	0.8680	0.43	0.17
3	50	159	162	4.7	0.6410	0.41	0.18
3	70	196	198	6.6	0.4430	0.38	0.21
3	95	238	236	9.0	0.3200	0.36	0.23
3	120	274	268	11.3	0.2530	0.34	0.25
3	150	309	302	14.2	0.2060	0.33	0.27
3	185	354	342	17.5	0.1640	0.32	0.29
3	240	415	395	22.7	0.1250	0.31	0.32
3	300	472	444	28.3	0.1000	0.30	0.35
3	400	545	504	37.8	0.0778	0.29	0.39

DIMENSIONS 18/30kV

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP4830KV03050	3	50	26.0	76.0	6700
MP4830KV03070	3	70	27.5	80.0	7445
MP4830KV03095	3	95	29.5	85.5	9015
MP4830KV03120	3	120	31.0	89.5	9895
MP4830KV03150	3	150	32.5	92.5	10515
MP4830KV03185	3	185	34.0	96.0	11420
MP4830KV03240	3	240	36.0	101.5	12750
MP4830KV03300	3	300	39.0	108.0	14320
MP4830KV03400	3	400	42.0	115.0	16220



ELECTRICAL CHARACTERISTICS 18/30kV

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT, T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE μF/km
		In air	Buried				
3	50	159	162	4.7	0.6410	0.45	0.14
3	70	196	198	6.6	0.4430	0.41	0.16
3	95	238	236	9.0	0.3200	0.39	0.17
3	120	274	268	11.3	0.2530	0.38	0.19
3	150	309	302	14.2	0.2060	0.37	0.20
3	185	354	342	17.5	0.1640	0.35	0.21
3	240	415	395	22.7	0.1250	0.34	0.24
3	300	472	444	28.3	0.1000	0.32	0.26
3	400	545	504	37.8	0.0778	0.31	0.29

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.