

NA2X2Y Cable 1.8/3kV IEC 60502-1 AL/XLPE/MDPE



APPLICATION

Low Voltage power and auxiliary fixed wiring cables for the supply of electrical energy. Suitable for external installation including damp and wet conditions (AD7).

CHARACTERISTICS

Voltage Rating

1.8/3 (3.6)kV

Temperature Range

Maximum Conductor Operating Temperature: +90°C

Maximum Conductor Temperature During S.C: +250°C

Minimum Bending Radius

15 x Overall Diameter

CONSTRUCTION

Conductor

Class 2 Stranded Plain Aluminium Circular Compact Conductor

Insulation

XLPE (Cross linked Polyethylene)

Sheath

MDPE (Low Density Polyethylene)

Sheath Colour

● Black

STANDARDS

IEC 60502-1, IEC 60228, Generally to HD 603 5G

UV resistant ISO 4892

Halogen free to IEC 60754

Water resistant to AD7

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].



DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL INSULATION THICKNESS mm	NOMINAL SHEATH THICKNESS mm	NOMINAL OUTER DIAMETER mm	NOMINAL WEIGHT kg/km
A902Y3KV01016	1	16	2	1.4	11.5	125
A902Y3KV01025	1	25	2	1.4	12.6	160
A902Y3KV01035	1	35	2	1.4	13.7	195
A902Y3KV01050	1	50	2	1.4	15	240
A902Y3KV01070	1	70	2	1.5	16.8	325
A902Y3KV01095	1	95	2	1.5	18.3	400
A902Y3KV01120	1	120	2	1.6	19.9	490
A902Y3KV01150	1	150	2	1.6	22.1	590
A902Y3KV01185	1	185	2	1.7	23.2	705
A902Y3KV01240	1	240	2	1.8	25.8	875
A902Y3KV01300	1	300	2	1.8	28.2	1065
A902Y3KV01400	1	400	2	1.9	30.9	1330
A902Y3KV01500	1	500	2.2	2.0	34.9	1680
A902Y3KV01630	1	630	2.4	2.2	39	2165
A902Y3KV01800	1	800	2.6	2.3	44.4	2800
A902Y3KV011000	1	1000	2.8	2.4	51.3	3535

ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA mm ²	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C Ω/Km	MAXIMUM CONDUCTOR AC RESISTANCE AT 50 Hz Ω/Km	CURRENT CAPACITY RATING		
			Laid in ground	Laid in duct	Laid in free air
16	1.91	2.435	106	77	89
25	1.2	1.53	136	99	117
35	0.868	1.107	163	119	143
50	0.641	0.817	192	142	174
70	0.443	0.565	236	176	220
95	0.32	0.408	281	213	269
120	0.253	0.323	321	245	315
150	0.206	0.263	359	277	360
185	0.164	0.209	408	318	417
240	0.125	0.159	474	375	498
300	0.1	0.128	536	430	578
400	0.0778	0.099	613	497	680
500	0.0605	0.077	699	579	801
630	0.469	0.06	795	670	936
800	0.0367	0.047	897	769	1090
1000	0.0291	0.037	999	878	1260

Laying conditions at trefoil formation are as below:

- Soil thermal resistivity: 120°C.Cm/Watt
- Burial depth: 0.5m
- Ground Temperature: 15°C | Air temperature: 25°C | Frequency: 50Hz

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.