

318-A / BS 6004 Arctic Grade Cable



Eland Product Group: A5A

APPLICATION

Arctic grade PVC cords manufactured to BS 6004 are designed to withstand severe external temperatures and will remain flexible at temperatures down to -40°C. Making them particularly suitable for outdoor applications and for use where flexibility is required at sub zero temperatures. At normal temperatures the cable is very flexible, offering some of the characteristics usually found in elastomeric cables.

CHARACTERISTICS

Voltage Rating Uo/U
300/500V

Temperature Rating
Fixed: -40°C to +60°C

Minimum Bending Radius
Fixed: 6 x overall diameter

CONSTRUCTION

Conductor
Class 5 flexible copper conductor

Insulation
Arctic grade PVC (Polyvinyl Chloride)

Sheath
Arctic grade PVC (Polyvinyl Chloride)

Core Identification
2 core: ● Blue ● Brown
3 core: ● Blue ● Brown ● Green/Yellow

Sheath Colour
● Blue ● Yellow

CABLE THIRD-PARTY ACCREDITATIONS

We supply BASEC approved products
Cables are tested and certified by BASEC, The British Approvals Service for Cables

STANDARDS

BS 6004, EN 60228

Flame Retardant according to IEC/EN 60332-1-2

THE CABLE LAB®

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab®.





DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL THICKNESS OF INSULATION mm	NOMINAL THICKNESS OF SHEATH mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A5A2075*1R	2	0.75	0.6	0.8	6.2	55
A5A2010*1R	2	1	0.6	0.8	6.4	61
A5A2015*1R	2	1.5	0.7	0.8	7.4	83
A5A2025*1R	2	2.5	0.8	1	9.2	130
A5A204*1R	2	4	0.8	1.1	10.4	176
A5A206*1R	2	6	0.8	1.2	11.3	73
A5A3010*1R	3	1	0.6	0.8	6.8	105
A5A3015*1R	3	1.5	0.7	0.9	8.1	163
A5A3025*1R	3	2.5	0.8	1.1	10	224
A5A304*1R	3	4	0.8	1.2	11.3	299
A5A306*1R	3	6.0	0.8	1.2	12.7	299

* Designates the sheath colour. For each Eland Cables part number replace with the colour code as listed below e.g. A5A2075B1R = 0.75mm² Blue

COLOUR CODES

COLOUR	Blue	Yellow
CODE	B	Y

CONDUCTORS

Class 5 Flexible Copper Conductors for Single Core and Multi-Core Cables

NOMINAL CROSS SECTIONAL AREA mm ²	MAXIMUM DIAMETER OF WIRES IN CONDUCTOR mm	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km
		Plain Wires
0.75	0.21	26
1	0.21	19.5
1.5	0.26	13.3
2.5	0.26	7.98
4	0.31	4.95
6	0.31	3.30

ELECTRICAL CHARACTERISTICS

Current Carrying Capacity

NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY AT 30°C Amps	
	Single-Phase AC	Three-Phase AC
0.75	6	6
1	10	10
1.5	16	16
2.5	25	20
4	32	25
6	48	40

VOLTAGE DROP

NOMINAL CROSS SECTIONAL AREA mm ²	DC OR SINGLE-PHASE AC mV/A/m	THREE-PHASE AC mV/A/m
0.75	62	54
1	46	40
1.5	32	27
2.5	19	16
4	12	10
6	8	7

Conductor operating temperature: 60°C

The above table is in accordance with Table 4F3B of the 18th Edition of IEE Wiring Regulations BS7671 and IEC 60364-5-52.

DE-RATING FACTORS

AMBIENT TEMPERATURE	35°C	40°C	45°C	50°C	55°C
DE-RATING FACTOR	0.91	0.82	0.71	0.58	0.41

The above table is in accordance with Table 4F3A of the 18th Edition of IEE Wiring Regulations BS7671 and IEC 60364-5-52.