

FL2XCYRY Cable



Eland Product Group: F04

APPLICATION

These cables are used as airfield lighting equipment primary cables for the series circuit connecting the Constant Current Regulators and the isolating transformers, and between the isolating transformers. Impact and weather resistant.

CHARACTERISTICS

Rated Voltage U_0/U (Um)

6/10kV

Temperature Rating

Operating: -40°C to +90°C

Minimum Bending Radius

15 x Overall Diameter

CONSTRUCTION

Conductor

Stranded bare copper conductor

Inner Semi-Conducting Layer

Extruded semi-conducting compound

Insulation

XLPE (Cross-linked Polyethylene)

Outer Semi-Conducting Layer

Extruded semi-conducting compound

Shield

Concentric layer of bare copper wires, counter helix of copper tape

Inner Sheath

PVC (Polyvinyl chloride)

Armour

GSWA (Galvanised steel wire armour)

Outer Sheath

PVC (Polyvinyl chloride) - Flame retardant, UV & Oil resistant

Sheath Colour

● Red

DIMENSIONS

ELAND PART NO.	NUMBER OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL INSULATION THICKNESS mm	NOMINAL SHEATH THICKNESS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
F0410KV010060RD	1	6	3.5	1.4	20.5	710

STANDARDS

ENV 50213, IEC 50602-2

THE CABLE LAB®

AN ISO/IEC 17025 AND IECCE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab®.

