

400Hz Airport 3-core With Control Wires Cable



Eland Product Group: F17

APPLICATION

These 3-core cables with control wires designed for 400 Hz systems for power supply of aircraft, computer systems and radar stations. They are suitable for laying in earth, in water, outdoors, indoors and in cable ducts.

CHARACTERISTICS

Rated Voltage Uo/U (Um) 0.6/1kV

Temperature Rating Fixed: -40°C to +90°C

Minimum Bending Radius Static: 3x Overall Diameter Dynamic: 4x Overall Diameter

CONSTRUCTION

Conductor Class 6 Stranded copper conductor

Insulation XLEPR (Cross-linked Ethylene Propylene Rubber)

Control Core

1mm² stranded copper conductor with XLPE insulation

Metallic Screen (Neutral Conductor) Concentric Copper Wires

Cable Assembling

Control cores, neutral conductor and dummy elements around phase conductors

Sheath PUR (Polyurethane) with abrasion indicators

Sheath Colour

Yellow

DIMENSIONS

STANDARDS

VDE 0295, IEC 60228

THE CABLE LAB®

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab®.



ELAND PART NO.	NUMBER OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL CROSS SECTIONAL AREA SCREEN mm ²	NO. CONTROL CORES	NOMINAL DIAMETER SINGLE CORE mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
F17LV03035YW	3	35	20	8	20.5	44.1	2790
F17LV03070YW	3	70	25	8	22.2	47.8	3560