

Cord End Terminals



Eland Product Group: **FET**

APPLICATION

Cord End Terminals are designed to terminate the end of a cable, prior to fitting screw type terminal blocks or connectors. The crimped on cord end terminal then protects the exposed wire strands from damage from the screw, which results in a stronger connection.

CONSTRUCTION

Material

Tinned copper

STANDARDS

DIN 46228 Part 4

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



SCIENCE
BASED
TARGETS

BUSINESS
AMBIITION FOR **1.5°C**



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].





DIMENSIONS

French Colour Range

ELAND PART NO.	CABLE SIZE mm ²	COLOUR	TOTAL LENGTH mm	PIN LENGTH mm	PIN WIDTH mm	PIN WALL THICKNESS mm	ENTRY WIDTH mm
FET0.25F	0.25	Violet	10.4	6	0.8	0.15	1.8
FET0.5F	0.5	White	14	8	1	0.15	2.6
FET0.75F	0.75	Blue	14.6	8.2	1.2	0.15	2.8
FET1F	1	Red	14.6	8.2	1.4	0.15	3
FET1.5F	1.5	Black	14.6	8.2	1.7	0.15	3.5
FET2.5F	2.5	Grey	15.2	8.2	2.2	0.15	4
FET4F	4	Orange	16.5	9	2.8	0.2	4.4
FET6F	6	Green	20	12	3.5	0.2	6.3
FET10F	10	Brown	21.5	12	4.5	0.2	7.6
FET16F	16	Ivory	22.2	12	5.8	0.2	8.8
FET25F	25	Black	29	16	7.3	0.2	11.2
FET35F	35	Red	30	16.2	8.3	0.2	12.5
FET50F	50	Blue	36	19	10.3	0.3	15

German Colour Range

ELAND PART NO.	CABLE SIZE mm ²	COLOUR	TOTAL LENGTH mm	PIN LENGTH mm	PIN WIDTH mm	PIN WALL THICKNESS mm	ENTRY WIDTH mm
FET0.25	0.25	Light Blue	10.4	6	0.8	0.15	1.8
FET0.34	0.34	Turquoise	10.4	6	0.8	0.15	2
FET0.5	0.5	Orange	14	8	1	0.15	2.6
FET0.75	0.75	White	14.6	8.2	1.2	0.15	2.8
FET1	1	Yellow	14.6	8.2	1.4	0.15	3
FET1.5	1.5	Red	14.6	8.2	1.7	0.15	3.5
FET2.5	2.5	Blue	15.2	8.2	2.2	0.15	4
FET4	4	Grey	16.5	9	2.8	0.2	4.4
FET6	6	Black	20	12	3.5	0.2	6.3
FET10	10	Ivory	21.5	12	4.5	0.2	7.6
FET16	16	Green	22.2	12	5.8	0.2	8.8
FET25	25	Brown	29	16	7.3	0.2	11.2
FET35	35	Beige	30	16.2	8.3	0.2	12.5
FET50	50	Olive	36	19	10.3	0.3	15

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.