

Uninsulated Cord End Terminals



Eland Product Group: **FCA**

APPLICATION

Uninsulated cord end terminals are designed to terminate the end of a cable, prior to fitting screw type terminal blocks or connectors. The crimped on uninsulated cord end terminal then protects the exposed wire strands from damage from the screw, which results in a stronger connection.

CONSTRUCTION

Material

Tinned copper

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



SCIENCE
BASED
TARGETS

BUSINESS
AMBITION FOR **1.5°C**



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].



DIMENSIONS

ELAND PART NO.	CABLE SIZE mm ²	LENGTH mm	WIDTH mm	WALL THICKNESS mm
FCUT 0.25-5	0.25	5	0.8	0.15
FCUT 0.5-6	0.5	6	1.0	0.15
FCUT 0.5-10	0.5	10	1.0	0.15
FCUT 0.75-6	0.75	6	1.2	0.15
FCUT 0.75-10	0.75	10	1.2	0.15
FCUT 1.0-6	1	6	1.4	0.15
FCUT 1.0-10	1	10	1.4	0.15
FCUT 1.5-7	1.5	7	1.7	0.15
FCUT 1.5-10	1.5	10	1.7	0.15
FCUT 2.5-7	2.5	7	2.2	0.15
FCUT 2.5-10	2.5	10	2.2	0.15
FCUT 4.0-9	4	9	2.8	0.20
FCUT 4.0-12	4	12	2.8	0.20
FCUT 6.0-12	6	12	3.5	0.20
FCUT 6.0-15	6	15	3.5	0.20
FCUT 10.0-12	10	12	4.5	0.20
FCUT 10.0-15	10	15	4.5	0.20
FCUT 10.0-18	10	18	4.5	0.20
FCUT 16.0-12	16	12	5.8	0.20
FCUT 16.0-15	16	15	5.8	0.20
FCUT 16.0-18	16	18	5.8	0.20
FCUT 25-15	25	15	7.3	0.20
FCUT 25-18	25	18	7.3	0.20
FCUT 25-25	25	25	7.3	0.20
FCUT 35-18	35	18	8.3	0.20
FCUT 35-25	35	25	8.3	0.20
FCUT 35-32	35	32	8.3	0.20
FCUT 50-18	50	18	10.3	0.30
FCUT 50-25	50	25	10.3	0.30
FCUT 50-32	50	32	10.3	0.30
FCUT 70-25	70	25	12.5	0.35
FCUT 95-30	95	30	14.5	0.35
FCUT 120-34	120	34	16.5	0.45
FCUT 150-38	150	38	18.5	0.50

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.