

400Hz Airport 7-core with Copper Wire Braid Shield Cable



ELAND CABLES ©

Eland Product Group: F21

APPLICATION

This 7 core copper wire braided cable is designed for 400Hz systems for power supply of aircraft, computer systems and radar stations. It is suitable for laying in earth, in water, outdoors, indoors and in cable ducts.

CHARACTERISTICS

Rated Voltage U_o/U
0.6/1kV

Temperature Rating
Fixed: -20°C to +70°C

Minimum Bending Radius
Static: 6x Overall Diameter
Dynamic: 12x Overall Diameter

CONSTRUCTION

Conductor
Class 2/Class 5 Stranded bare copper

Insulation
XLPE (cross linked polyethylene)

Metallic Screen
Bare copper wire braid

Sheath
PVC (Polyvinyl chloride)

Sheath Colour
● Black

STANDARDS

VDE 0271, VDE 0295, IEC 60228

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability

SCIENCE
BASED
TARGETSBUSINESS
AMBIITION FOR 1.5°C

REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].



DIMENSIONS

ELAND PART NO.	NUMBER OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER OF SINGLE CORE mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
F21LV07070BK	7	70	11.9	46.5	6430