


Hook Up Wire 300V



ELAND CABLES ©

Eland Product Group: A2U

APPLICATION

For general purpose internal wiring of electronic and electrical equipment, where exposed to oil at a temperature not exceeding 60°C or 80°C. Uniform insulation thickness of wire to ensure easy stripping and cutting. Resistant to acids, alkalis, oils, moisture and fungi.

CHARACTERISTICS

Voltage Rating
300V

Temperature Rating
+80°C

CONSTRUCTION

Conductor
Class 2 Stranded Copper

Insulation
PVC (Polyvinyl Chloride)

Core Identification
● Black ● Blue ● Brown ● Green ● Grey ● Yellow ○ White
● Violet ● Pink

Note
Tinned Copper conductor available on request

STANDARDS

UL 1007, UL 758, UL1581, CSA C22-2, IEC 60228

Flame propagation: UL VW-1, CSA FT1

THE CABLE LAB®

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab®.





DIMENSIONS

Overall Tinned Conductor

| ELAND PART NO. | AWG SIZE | CONDUCTOR STRANDING | NOMINAL DIAMETER OF CONDUCTOR mm | NOMINAL THICKNESS OF INSULATION mm | NOMINAL DIAMETER OF INSULATION mm |
|----------------|----------|---------------------|-------------------------------------|---------------------------------------|--------------------------------------|
| A2U18AWG** | 18 | 7/0.404 | 1.21 | 0.41 | 2.03 |
| A2U20AWG** | 20 | 7/0.321 | 0.96 | 0.41 | 1.78 |
| A2U22AWG** | 22 | 7/0.254 | 0.76 | 0.41 | 1.58 |
| A2U24AWG** | 24 | 7/0.203 | 0.61 | 0.41 | 1.43 |

* Designates the sheath colour. For each Eland Cables part number replace with the colour code as listed below. e.g. A3Y020050BK = 0.5mm² Black

COLOUR CODES

| COLOUR | White | Blue | Brown | Green | Grey | Yellow | Violet | Pink | Black |
|--------|-------|------|-------|-------|------|--------|--------|------|-------|
| CODE | WH | BL | BR | GN | GR | YW | VI | PK | BK |

ELECTRICAL CHARACTERISTICS

Overall Tinned Conductor

| AWG | MAXIMUM RESISTANCE AT 20°C ohms/km | MINIMUM INSULATION RESISTANCE AT 20°C ohms/km | DIELECTRIC STRENGTH AC 1MIN V | STANDARD LENGTH Ft(M) |
|-----|---------------------------------------|--|----------------------------------|--------------------------|
| 18 | 23.2 | 15 | 1500 | 2000 (610) |
| 20 | 34.2 | 15 | 1500 | 2000 (610) |
| 22 | 54.8 | 15 | 1500 | 2000 (610) |
| 24 | 86 | 15 | 1500 | 2000 (610) |

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.