

NF C33-224 / NF C33-225 Cable



ELAND CABLES @

Eland Product Group: F01

APPLICATION

These cables are used as airfield lighting equipment primary cables for the series circuit connecting the Constant Current Regulators and the isolating transformers, and between the isolating transformers.

CHARACTERISTICS

Rated Voltage Uo/U (Um) 3.6/6 (7.2kV) 6/10 (12kV)

Temperature Rating Fixed: -20°C to +70°C

Minimum Bending Radius Static: 10 x Overall Diameter Dynamic: 20 x Overall Diameter

CONSTRUCTION

Conductor Stranded bare or tinned copper conductor

Inner Semi-Conductor Extruded semi-conducting compound

Insulation XLPE (Cross-linked Polyethylene) - EPDM on request

Outer Semi-Conductor

Extruded semi-conducting compound

Shield

Copper tape shield - Copper wire screen on request.

Sheath XLPE (Cross-linked Polyethylene) - PVC/HFFR/CR on request.

Sheath Colour

Black (6kV)

STANDARDS

NF C33-224, NF C33-225

THE CABLE LAB®

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab®.



DIMENSIONS

ELAND PART NO.	VOLTAGE kV	NOMINAL CROSS SECTIONAL AREA mm ²	NO. OF STRANDS	NOMINAL INSULATION THICKNESS mm	NOMINAL SHEATH THICKNESS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
F0106KV010060BK	3.6/6	6	7	2.7	1.4	12.5	198
F0110KV010060RD	6/10	6	7	3.6	1.6	14.7	250