



## FLRYY Cable



Eland Product Group: B3L

### APPLICATION

These low-voltage cables are designed for the wiring of electrical installations in the manufacture of commercial vehicles. Due to the ADR-approval especially suitable for trailers and semitrailers manufactured for the transport of GGVS hazardous substances.

### CHARACTERISTICS

#### Test Voltage

2 kV min. 5 minutes

#### Temperature Rating

Fixed: -40°C to +85°C

#### Minimum Bending Radius

12x overall diameter

#### Capacitance

Data Pair: Maximum 50pF/m

Between Data Pairs and other cores: Maximum 100pF/m

#### Insulation Resistance

Minimum 20 MOhm x km

### CONSTRUCTION

#### Conductor

Fine-wire bare copper conductor

#### Insulation

Cold-resistant special PVC (Polyvinyl Chloride)

#### Outer Sheath

Special PVC (Polyvinyl Chloride)

#### Core Identification

○ White numbered

#### Sheath Colour

● Black

### STANDARDS

DIN VDE 0295, IEC 60228, DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1, DIN VDE 0472

Conforming with national standard ISO 4141 and DIN/ISO 6722  
ADR approved

### THE CABLE LAB<sup>®</sup>

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



### SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: [www.elandcables.com/company/about-us/esg-sustainability](http://www.elandcables.com/company/about-us/esg-sustainability)



### REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab<sup>®</sup>.





## DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	AWG NO.	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
B3L02000005	2	0.5	20	4.8	40.0
B3L0200010	2	1	17	6.0	56.0
B3L0200010	2	1	17	6.0	56.0
B3L0200015	2	1.5	16	6.6	66.0
B3L02100075	2 + 2	0.75 + 1.5	18	7.0	91.0
B3L03000075	3	0.75	17	5.3	52.4
B3L0300010	3	1	17	6.3	66.0
B3L0310025	3 + 4	2.5 + 1.5	14	10.3	221.0
B3L0400010	4	1	17	6.8	80.0
B3L0400015	4	1.5	16	7.5	106.0
B3L0410060	4 + 1	6 + 1.5	18	13.7	411.0
B3L0500010	5	1	17	7.5	98.0
B3L0510010	5 + 1	1 + 2.5	17	9.0	132.0
B3L07000075	7	0.75	18	7.3	101.0
B3L0700015	7	1.5	16	10.3	185.0
B3L0810015	8 + 5	1.5 + 2.5	16	14.8	360.0
B3L0910015	9 + 4	1.5 + 2.5	16	14.8	350.0
B3L1010015	10 + 3	1.5 + 2.5	16	12.5	366.0
B3L1020015	10 + 3 + 2	1.5 + 2.5 + 1.5	16	14.4	393.0
B3L1110015	11 + 3	1.5 + 2.5	16	13.5	365.0

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.