



BS 6622 Aluminium AWA/SWA PVC 3.8/6.6kV Cable



Eland Product Group: A9M

APPLICATION

Armoured power distribution cables with aluminium conductors for external and direct burial applications in power networks.

CHARACTERISTICS

Voltage Rating Uo/U (Um)
3.8/6.6 (7.2)kV

Test Voltage (AC)
12.5kV

Temperature Rating

Maximum operating temperature: 90°C
Maximum short circuit temperature: 250°C

Minimum Bending Radius

Single core: 15x overall diameter
Multi core: 12 x overall diameter

(Single core 12 x overall diameter and 3 core 10 x overall diameter where bends are positioned adjacent to a joint or termination provided that the bending is carefully controlled by the use of a former)

CONSTRUCTION

Conductor

Class 2 compacted aluminium conductor

Conductor Screen

Semi-conductive XLPE (Cross-Linked Polyethylene)

Insulation

XLPE (Cross-Linked Polyethylene)

Insulation Screen

Semi-conductive XLPE (Cross-Linked Polyethylene)

Insulation Screen

Concentric copper wires and copper tape

Inner Sheath

PVC (Polyvinyl Chloride)

Armour

Single core: AWA (Aluminium Wire Armoured)
Multi core: SWA (Galvanised steel wire)

Sheath

PVC (Polyvinyl Chloride)

Sheath Colour

● Red

BSI KITEMARK™ TESTED



Cables are tested and verified by The Cable Lab[®] to confirm they meet the quality standards required of the BSI Cable Testing Verification Kitemark™.

STANDARDS

BS 6622, IEC 60502-2, IEC/EN 60228, HD 620
Flame Retardant according to IEC/EN 60332-1-2

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



SCIENCE
BASED
TARGETS

**BUSINESS
AMBITION FOR 1.5°C**



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].





DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
B4A066KV01035R	1	35	24.40	823
B4A066KV01050R	1	50	25.60	894
B4A066KV01070R	1	70	27.70	1.034
B4A066KV01095R	1	95	29.60	1.179
B4A066KV01120R	1	120	30.80	1.285
B4A066KV01150R	1	150	32.50	1.508
B4A066KV01185R	1	185	35.20	1.773
B4A066KV01240R	1	240	37.90	2.038
B4A066KV01300R	1	300	40.80	2.357
B4A066KV01400R	1	400	45.00	2.893
B4A066KV01500R	1	500	49.80	3.553
B4A066KV01630R	1	630	56.20	4.164
B4A066KV03050R	3	50	49	3750
B4A066KV03070R	3	70	54	4500
B4A066KV03095R	3	95	57	5000
B4A066KV03120R	3	120	60	5500
B4A066KV03150R	3	150	64	6000
B4A066KV03185R	3	185	68	6750
B4A066KV03240R	3	240	76	8750
B4A066KV03300R	3	300	82	10000
B4A066KV03400R	3	400	90	12000
B4A066KV03500R	3	500	97	14000

ELECTRICAL CHARACTERISTICS

Single Core

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km	OPERATING INDUCTANCE mH/km		OPERATING CAPACITY uF/km	CONTINUOUS CURRENT RATING Amps			
			Flat	Trefoil		In Ground		In Air	
						Flat	Trefoil	Flat	Trefoil
1	35	0.868	0.748	0.401	0.266	-	-	-	-
1	50	0.641	0.719	0.381	0.297	186	178	233	188
1	70	0.443	0.684	0.357	0.339	234	217	280	235
1	95	0.320	0.659	0.342	0.381	287	259	344	286
1	120	0.253	0.636	0.327	0.416	338	298	392	329
1	150	0.206	0.620	0.319	0.454	388	333	441	376
1	185	0.164	0.602	0.310	0.495	449	377	510	428
1	240	0.125	0.579	0.300	0.556	530	438	587	508
1	300	0.100	0.562	0.295	0.617	605	495	682	586
1	400	0.0788	0.543	0.290	0.681	678	562	781	676
1	500	0.0605	0.525	0.283	0.758	762	633	883	772
1	630	0.0469	0.507	0.276	0.853	858	712	1007	882



ELECTRICAL CHARACTERISTICS

Multi Core

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km	OPERATING INDUCTANCE mH/km	OPERATING CAPACITY uF/km	CONTINUOUS CURRENT RATING Amps	
					In Ground at 20°C	In Air at 30°C
3	50	0.641	0.33	0.31	162	160
3	70	0.443	0.31	0.37	199	199
3	95	0.320	0.30	0.41	238	242
3	120	0.253	0.29	0.44	271	280
3	150	0.206	0.28	0.49	304	318
3	185	0.164	0.27	0.53	345	365
3	240	0.125	0.27	0.57	401	431
3	300	0.100	0.26	0.58	516	649
3	400	0.0778	0.26	0.61	572	737
3	500	0.0605	0.25	0.65	638	835