

Cable Gland A2



Eland Product Group: **A8D**

APPLICATION

A2 brass cable glands are suitable for use with unarmoured cables. The outer seal grips the sheath of the cable to achieve a weather proof seal.

CONSTRUCTION

Gland Material
Brass

CHARACTERISTICS

Cable Type
Unarmoured cables

STANDARDS

BS 6121 Part 1

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].



DIMENSIONS

ELAND PART NO.	GLAND SIZE	ENTRY THREAD		CABLE ACCEPTANCE DETAILS		HEXAGONAL DETAILS		ASSEMBLED LENGTH E mm
		Diameter N mm	Length D mm	Minimum Nominal Overall Diameter A mm	Maximum Nominal Overall Diameter A mm	A/F F mm	A/C C mm	
FCGA220S	20S	20	15	8	11.8	22	24.4	21
FCGA220	20	20	15	11	13.8	24	26.6	21
FCGA225	25	25	15	13	19.8	30	33.3	23
FCGA232	32	32	15	19	26.4	41	45.5	28
FCGA240	40	40	20	25	32.4	46	51	31
FCGA250S	50S	50	20	31.5	38	58	64.4	33
FCGA250	50	50	20	36.5	44	60	66.6	33
FCGA263S	63S	63	20	42.5	49	70	77.7	35
FCGA263	63	63	20	48.5	55.5	75	83.2	35
FCGA275S	75S	75	20	54.5	62	84	93.2	36
FCGA275	75	75	20	60.5	67	90	100	36

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.