



BS 7835 XLPE LSZH 8.7/15kV Cable



Eland Product Group: A9M

APPLICATION

Medium voltage LSZH power cables for power networks, underground and in cable ducting.

CHARACTERISTICS

Voltage Rating Uo/U (Um)
8.7/15 (17.5) kV

Temperature Rating
Fixed: 0°C to +90°C

Minimum Bending Radius
Single core - Fixed: 15 x overall diameter
3 core - Fixed: 12 x overall diameter

(Single core 12 x overall diameter and 3 core 10 x overall diameter where bends are positioned adjacent to a joint or termination provided that the bending is carefully controlled by the use of a former)

CONSTRUCTION

Conductor
Class 2 stranded copper conductor

Conductor Screen
Semi-conductive XLPE (Cross-Linked Polyethylene)

Insulation
XLPE (Cross-Linked Polyethylene)

Insulation Screen
Semi-conductive XLPE (Cross-Linked Polyethylene)

Metallic Screen
Individual or collective overall copper tape screen

Filler
PET (Polyethylene Terephthalate) fibres

Separator
Binding tape

Bedding
LSZH (Low Smoke Zero Halogen)

Armour
Single core: AWA (Aluminium Wire Armoured)
Multi-core: SWA (Steel Wire Armoured)

Sheath
LSZH (Low Smoke Zero Halogen)

Sheath Colour
● Red ● Black

BSI KITEMARK™ TESTED



Cables are tested and verified by The Cable Lab® to confirm they meet the quality standards required of the BSI Cable Testing Verification Kitemark™.

STANDARDS

BS 7835, IEC/EN 60228,

Low Smoke Zero Halogen to IEC/EN 61034-1/2, IEC/EN 60754-1/2,
Flame Retardant acc. to IEC/EN 60332-1-2, IEC/EN 60332-3-24

THE CABLE LAB®

AN ISO/IEC 17025 AND IECCE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



SCIENCE
BASED
TARGETS

**BUSINESS
AMBITION FOR 1.5°C**



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab®.





DIMENSIONS

ELAND PART NO.	NUMBER OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	MINIMUM THICKNESS mm		NOMINAL THICKNESS OF SEMI CONDUCTIVE LAYER mm		NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Insulation	Outer sheath	Inner	Outer	Over insulation	Overall	
A9M15KV01050*	1	50	3.95	1.32	0.50	0.80	19.50	29	1300
A9M15KV01070*	1	70	3.95	1.40	0.50	0.80	21.10	31	1600
A9M15KV01095*	1	95	3.95	1.48	0.50	0.80	22.80	34	2000
A9M15KV01120*	1	120	3.95	1.48	0.50	0.80	24.10	35	2250
A9M15KV01150*	1	150	3.95	1.56	0.50	0.80	26.00	37	2600
A9M15KV01185*	1	185	3.95	1.56	0.50	0.80	27.30	39	3000
A9M15KV01240*	1	240	3.95	1.64	0.50	0.80	30.00	42	3600
A9M15KV01300*	1	300	3.95	1.72	0.50	0.80	32.10	45	4500
A9M15KV01400*	1	400	3.95	1.80	0.50	0.80	35.00	48	5400
A9M15KV01500*	1	500	3.95	1.88	0.50	0.80	38.00	51	6500
A9M15KV01630*	1	630	3.95	1.96	0.50	0.80	42.10	56	8000
A9M15KV03050*	3	50	3.95	2.12	0.50	0.80	19.50	57	5250
A9M15KV03070*	3	70	3.95	2.20	0.50	0.80	21.10	61	6250
A9M15KV03095*	3	95	3.95	2.28	0.50	0.80	22.80	65	7300
A9M15KV03120*	3	120	3.95	2.36	0.50	0.80	24.10	68	8300
A9M15KV03150*	3	150	3.95	2.52	0.50	0.80	26.00	74	10250
A9M15KV03185*	3	185	3.95	2.60	0.50	0.80	27.30	77	11500
A9M15KV03240*	3	240	3.95	2.76	0.50	0.80	30.00	83	13800
A9M15KV03300*	3	300	3.95	2.84	0.50	0.80	32.10	88	16200
A9M15KV03400*	3	400	3.95	3.08	0.50	0.80	35.00	95	19300
A9M15KV03500*	3	500	3.95	3.24	0.50	0.80	38.00	103	23100

* Designates the sheath colour. For each Eland Cables part number replace with the colour code as listed below e.g. A9M15KV01050RD = 50mm² Red

COLOUR CODES

COLOUR CODE	Red	Black
	RD	BK



Click here for more information:
elandcables.com [BS 7835 8.7/15kV Cable](#)

CONDUCTORS

Class 2 Stranded Conductors for Single Core and Multi-Core Cables

NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER OF CONDUCTOR	NOMINAL SHORT CIRCUIT CURRENT AT 1 SECOND kA	CONDUCTOR DC RESISTANCE AT 20 °C Ω/km	CONDUCTOR DC RESISTANCE AT 20 °C Ω/km
50	8.10	7.15	0.387	0.497
70	9.70	10.01	0.268	0.344
95	11.40	13.59	0.193	0.248
120	12.70	17.16	0.153	0.196
150	14.50	21.45	0.124	0.160
185	15.90	26.46	0.0991	0.128
240	18.60	34.32	0.0754	0.098
300	20.70	42.90	0.0601	0.080
400	23.50	57.20	0.0470	0.064
500	26.50	71.50	0.0366	0.0510
630	30.20	90.09	0.0283	0.0420

ELECTRICAL CHARACTERISTICS

Current Carrying Capacity

NUMBER OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY A		CONDUCTOR LOSSES IN THE GROUND kW/km
		In ground (20 °C)	In air (30 °C)	
1	50	249	277	30.81
1	70	303	345	31.58
1	95	358	418	31.78
1	120	404	481	31.99
1	150	441	537	31.12
1	185	493	612	31.11
1	240	563	716	31.06
1	300	626	811	31.35
1	400	676	901	29.25
1	500	743	1006	28.15
1	630	-	-	-
3	50	210	206	65.75
3	70	256	257	67.63
3	95	307	313	70.12
3	120	349	360	71.62
3	150	392	410	73.76
3	185	443	469	75.36
3	240	513	553	77.40
3	300	576	635	79.60
3	400	650	731	81.10
3	500	-	-	-



DE-RATING FACTORS

AIR TEMPERATURE °C	25	30	35	40	45	50	55
DE-RATING FACTOR	1.00	0.96	0.92	0.88	0.83	0.78	0.73
GROUND TEMPERATURE °C	10	15	20	25	30	35	40
DE-RATING FACTOR	1.03	1.00	0.97	0.93	0.89	0.86	0.82
GROUND THERMAL RESISTIVITY km/W	0.9	1.0	1.2	1.5	2.0	2.5	3.0
DE-RATING FACTOR	1.06	1.04	1.00	0.92	0.82	0.74	0.68
DEPTH OF LAYING m	0.80	1.00	1.25	1.50	1.75	2.00	2.50
DE-RATING FACTOR	1.00	0.97	0.95	0.94	0.93	0.91	0.90

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.