

Stainless Steel Cable Ties



Eland Product Group: **FCA**

APPLICATION

Cable ties ideal for very hot/aggressive or hazardous environments. Flame retardant. High tensile strength. Secured by hand or with a stainless steel tensioning tool.

CHARACTERISTICS

Temperature

-80°C to +538°C

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



SCIENCE
BASED
TARGETS

BUSINESS
AMBIITION FOR **1.5°C**



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].



DIMENSIONS

ELAND PART NO.	LENGTH mm	WIDTH mm	LOOP TENSILE STRENGTH	PACK QUANTITY
TTSS150	150	4.6	45	100
TTSS200	200	4.6	45	100
TTSS300	300	4.6	45	100
TTSS360-4.6	360	4.6	45	100