

9541 PVC - LSF Alternative Cable



Eland Product Group: A3B

APPLICATION

9541 - PVC-LSF Alternative cable RS232 data cable is a general purpose overall screened cable. With protection against electrical interference, this cable is suitable for RS232 applications.

CHARACTERISTICS

Voltage Rating
300V

Temperature Rating
Fixed: -20°C to +80°C

CONSTRUCTION

Conductor
Class 2 stranded tinned copper conductor

Insulation
PVC (Polyvinyl Chloride)

Drain Wire
Tinned copper

Screen
Al/Foil (Aluminium Foil)

Sheath
PVC-LSF (Polyvinyl Chloride-Low Smoke Fume)

Core Identification

● Red ● Black ○ White ● Green ● Blue ● Orange
○ White/Black ● Red/Black ● Green/Black ● Orange/Black
● Blue/Black ● Black/White ● Red/White ● Green/White
● Blue/White

Sheath Colour
● Grey

THE CABLE LAB®

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



SCIENCE
BASED
TARGETS

**BUSINESS
AMBITION FOR 1.5°C**



REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/863/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab®.





DIMENSIONS

ELAND PART NO.	NO. OF CORES	AWG (NO. OF STRANDS)	NOMINAL DIAMETER OF STRANDS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A3B9541LSFGR	15	AWG24(7)	0.2	7.22	83

ELECTRICAL CHARACTERISTICS

CAPACITANCE AT 1kHz pF/m	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km
107	94.1