

# 9729 PVC - LSF Alternative Cable



Eland Product Group: A3B

#### **APPLICATION**

9729 - PVC-LSF Alternative cable is suitable for CAD/CAM & RS422 applications. This cable is used widely in the security and instrumentation industry, audio and computer applications, where there is a need for screening from external sources.

# **CHARACTERISTICS**

**Voltage Rating** 300V

**Temperature Rating** Fixed: -20°C to +80°C

## **CONSTRUCTION**

#### Conductor

Class 2 stranded tinned copper conductor

### Insulation

PE (Polyethylene)

#### Screen

Al/Foil (Aluminium Foil)

### **Drain Wire**

Tinned copper

## Sheath

PVC-LSF (Polyvinyl Chloride-Low Smoke Fume)

## **Core Identification**

Pair 1: 

Black 

Red Pair 2: ● Black ○ White

## **Sheath Colour**

Grey

# THE CABLE LAB®

## AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



### SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions. our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability





SCIENCE BASED TARGETS BUSINESS 1.5°C SCIENCE BASED TARGETS







## REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab®.







# **DIMENSIONS**

ELAND PART NO.	NO. OF PAIRS	AWG (NO. OF STRANDS)	NOMINAL DIAMETER OF STRANDS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A3B9729LSFGR	2	AWG24(7)	0.19	7.4	55

# **ELECTRICAL CHARACTERISTICS**

CAPACITANCE AT 1kHz pF/m	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km
50	91