

XHIO1RV 6/10kV Cable



Eland Product Group: MP27

APPLICATION

Portuguese referenced Medium Voltage cable for power distribution and power supply stations used in Utility and Industrial applications, for rated voltages up to 6/10kV. Suitable for fixed installations, directly buried. Good mechanical protection.

CHARACTERISTICS

Voltage Rating U_0/U (Um)
6/10 (12)kV

Temperature Rating
 Conductor maximum operating temperature: 90°C
 Maximum short-circuit temperature: 250°C

Minimum Bending Radius
 During installation: 20 x overall diameter
 After installation: 15 x overall diameter

CONSTRUCTION

Conductor
Class 2 stranded Copper

Conductor Screen
Semi-conductive XLPE (Cross-Linked Polyethylene)

Insulation
XLPE (Cross-Linked Polyethylene)

Insulation Screen
Semi-conductive XLPE (Cross-Linked Polyethylene)

Metallic Screen
Copper wire screen

Inner Sheath
PVC (Polyvinyl Chloride)

Armour
AWA - Aluminium wires, helically applied, tightened with plastic tapes

Sheath
PVC (Polyvinyl Chloride) type ST2

Sheath Colour
● Black

STANDARDS

IEC 60228, IEC 60502-2,
Flame retardant IEC 60332-1-2

ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab®, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.





DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP2710KV01025	1	25	15.0	27.5	1050
MP2710KV01035	1	35	16.0	28.5	1175
MP2710KV01050	1	50	17.0	29.5	1325
MP2710KV01070	1	70	18.5	31.5	1575
MP2710KV01095	1	95	20.5	33.0	1865
MP2710KV01120	1	120	22.0	35.0	2170
MP2710KV01150	1	150	23.0	36.0	2445
MP2710KV01185	1	185	24.5	37.5	2845
MP2710KV01240	1	240	27.0	40.0	3445
MP2710KV01300	1	300	30.0	43.0	4130
MP2710KV01400	1	400	33.0	46.0	5105
MP2710KV01500	1	500	36.0	49.5	6100
MP2710KV01630	1	630	41.5	53.0	7815

ELECTRICAL CHARACTERISTICS

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT. T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE µF/km
		In air	Buried				
1	25	166	163	3.6	0.7270	0.46	0.22
1	35	201	196	5.0	0.5240	0.44	0.24
1	50	240	231	7.2	0.3870	0.41	0.27
1	70	299	282	10.0	0.2680	0.39	0.30
1	95	364	338	13.6	0.1930	0.37	0.34
1	120	420	383	17.2	0.1530	0.36	0.37
1	150	474	428	21.5	0.1240	0.35	0.39
1	185	539	471	26.5	0.0991	0.34	0.42
1	240	636	555	34.3	0.0754	0.32	0.48
1	300	731	625	42.9	0.0601	0.31	0.53
1	400	846	708	57.2	0.0470	0.30	0.59
1	500	972	797	71.5	0.0366	0.29	0.65
1	630	1 110	892	90.1	0.0283	0.28	0.72

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.