

# Cable Ties - Nylon



Eland Product Group: **FCA**

## CONSTRUCTION

### Material

Natural and black nylon 6/6

## CHARACTERISTICS

### Temperature

-40°C to +85°C

## STANDARDS

UL94V2

### THE CABLE LAB<sup>®</sup>

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



## SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: [www.elandcables.com/company/about-us/esg-sustainability](http://www.elandcables.com/company/about-us/esg-sustainability)



SCIENCE  
BASED  
TARGETS

**BUSINESS  
AMBITION FOR 1.5°C**



## REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab<sup>®</sup>.





## DIMENSIONS

### Tie Width 2.5mm

ELAND PART NO.		LENGTH mm	WIDTH mm	MAXIMUM BUNDLE DIAMETER mm	MINIMUM TENSILE STRENGTH	PACK QUANTITY
NATURAL	BLACK					
FTR100-2.5	FTR100-2.5B	100	2.5	18	8.2	100
FTR160-2.5	FTR160-2.5B	160	2.5	40	8.2	100

### Tie Width 3.6mm

ELAND PART NO.		LENGTH mm	WIDTH mm	MAXIMUM BUNDLE DIAMETER mm	MINIMUM TENSILE STRENGTH	PACK QUANTITY
NATURAL	BLACK					
FTR100-3.6	FTR100-3.6B	100	3.6	18	8.2	100
FTR160-3.6	FTR160-3.6B	160	3.6	40	8.2	100

### Tie Width 4.8mm

ELAND PART NO.		LENGTH mm	WIDTH mm	MAXIMUM BUNDLE DIAMETER mm	MINIMUM TENSILE STRENGTH	PACK QUANTITY
NATURAL	BLACK					
FTR100-4.8	FTR100-4.8B	100	4.8	18	8.2	100
FTR160-4.8	FTR160-4.8B	160	4.8	40	8.2	100

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.