



# YMz1Krvasdldw 18/30kV Cable



Eland Product Group: B9X

## APPLICATION

LSZH Medium Voltage cable with copper conductors offering a lightweight alternative to aluminium conductor alternatives. Suitable for use in conduit and for fixed, protected installation. For installations where fire, smoke emission and toxic fume create a potential risk to life and equipment.

## CHARACTERISTICS

**Voltage Rating** Uo/U  
8.7/15kV

**Temperature Rating**  
Fixed: 0°C to +90°C  
Maximum Conductor Short-Circuit Temp up to 5 sec: 250°C

**Minimum Bending Radius**  
15 x overall diameter

## CONSTRUCTION

**Conductor**  
Class 2 Stranded Copper

**Inner Semi-Conductive Layer**  
Semi-Conductive Material

**Insulation**  
XLPE (Cross-Linked Polyethylene)

**Outer Semi-Conductive Layer**  
Semi-Conductive Material

**Screen**  
Copper wires and tape

**Outer Sheath**  
LSZH (Low Smoke Zero Halogen) UV Resistant

**Sheath Colour**  
● Red

## STANDARDS

Generally to HD 620-10J / NEN 3620  
Fire Resistant to IEC/EN 60332-1-2, IEC/EN 60332-3-24 Cat.C

## THE CABLE LAB®

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



## SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: [www.elandcables.com/company/about-us/esg-sustainability](http://www.elandcables.com/company/about-us/esg-sustainability)



## REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab®.





## DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	NOMINAL CROSS SECTIONAL AREA OF SCREEN mm <sup>2</sup>	NOMINAL DIAMETER OVER CONDUCTOR mm	NOMINAL THICKNESS OF INSULATION mm	NOMINAL THICKNESS OF SEMI-CONDUCTIVE LAYER mm		NOMINAL THICKNESS OF SHEATH mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
						Inner	Outer			
B9X30KV01050RD	1	50	25	8.10	8.00	0.50	0.40(fully bonded)	2.50	35	1600
B9X30KV01070RD	1	70	25	9.70	8.00	0.50	0.40(fully bonded)	2.50	36	1800
B9X30KV01095RD	1	95	25	11.40	8.00	0.50	0.40(fully bonded)	2.50	38	2200
B9X30KV01120RD	1	120	25	12.65	8.00	0.50	0.40(fully bonded)	2.50	39	2400
B9X30KV01150RD	1	150	25	14.40	8.00	0.50	0.40(fully bonded)	2.50	41	2750
B9X30KV01185RD	1	185	25	15.75	8.00	0.50	0.40(fully bonded)	2.50	42	3100
B9X30KV01240RD	1	240	25	18.20	8.00	0.50	0.40(fully bonded)	2.50	45	3750
B9X30KV01300RD	1	300	25	20.50	8.00	0.50	0.40(fully bonded)	2.50	47	4400
B9X30KV01400RD	1	400	50	23.00	8.00	0.50	0.40(fully bonded)	2.50	50	5500
B9X30KV01500RD	1	500	50	26.00	8.00	0.50	0.40(fully bonded)	2.50	54	6600
B9X30KV01630RD	1	630	50	29.70	8.00	0.50	0.40(fully bonded)	2.50	58	8000

## ELECTRICAL CHARACTERISTICS

### Single Core

NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	NOMINAL SHORT-CIRCUIT OF CONDUCTOR CURRENT FOR 1 SECOND kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C Ω/km	CONDUCTOR AC RESISTANCE BY MAXIMUM TEMPERATURE Ω/km	CURRENT CARRYING CAPACITY A		CONDUCTOR LOSSES IN THE GROUND kW/km
				In Ground 20°C	In Air 30°C	
50	7.15	0.387	0.497	251	279	31.3
70	10.01	0.268	0.344	306	348	32.2
95	13.59	0.193	0.248	363	421	32.7
120	17.16	0.153	0.196	410	483	32.9
150	21.45	0.124	0.160	449	540	32.3
185	26.46	0.0991	0.128	503	615	32.4
240	34.32	0.0754	0.0980	576	718	32.5
300	42.90	0.0601	0.0800	641	812	32.9
400	57.20	0.0470	0.0640	697	904	31.1
500	71.50	0.0366	0.0510	769	1011	30.1
630	90.09	0.0283	0.0420	847	1043	-

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.