

LXHI1RV 18/30kV Cable



Eland Product Group: MP29

APPLICATION

Portuguese referenced Medium Voltage cable for power distribution and power supply stations used in Utility and Industrial applications, for rated voltages up to 18/30kV. Suitable for fixed installations, directly buried. Good mechanical protection.

CHARACTERISTICS

Voltage Rating U_o/U (U_m)
18/30 (36)kV

Temperature Rating

Conductor maximum operating temperature: 90°C
Maximum short-circuit temperature: 250°C

Minimum Bending Radius

During installation: 20 x overall diameter
After installation: 15 x overall diameter

CONSTRUCTION

Conductor

Class 2 stranded circular Aluminium

Conductor Screen

Semi-conductive XLPE (Cross-Linked Polyethylene)

Insulation

XLPE (Cross-Linked Polyethylene)

Insulation Screen

Semi-conductive XLPE (Cross-Linked Polyethylene)

Metallic Screen

Copper tape screen

Inner Sheath

PVC (Polyvinyl Chloride)

Armour

AWA - Aluminium wires, helically applied, tightened with plastic tapes

Sheath

PVC (Polyvinyl Chloride)

Sheath Colour

● Black

STANDARDS

IEC 60228, IEC 60502-2

Flame Retardant to IEC 60332-1-2

ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab®, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



8578



FS 672069



EMS 672067



OHS 672066

REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.



KN 036287





DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP2930KV01050	1	50	26.0	39.0	1595
MP2930KV01070	1	70	27.5	41.0	1760
MP2930KV01095	1	95	29.5	42.5	1920
MP2930KV01120	1	120	31.0	44.5	2105
MP2930KV01150	1	150	32.5	46.0	2250
MP2930KV01185	1	185	34.0	47.5	2460
MP2930KV01240	1	240	36.0	50.0	2780
MP2930KV01300	1	300	39.0	53.5	3125
MP2930KV01400	1	400	42.0	56.5	3585
MP2930KV01500	1	500	45.0	59.5	4020
MP2930KV01630	1	630	49.5	64.5	4765

ELECTRICAL CHARACTERISTICS

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT, T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE µF/km
		In air	Buried				
1	50	191	178	4.7	0.641	0.48	0.14
1	70	238	218	6.6	0.443	0.45	0.16
1	95	288	260	9.0	0.320	0.43	0.17
1	120	333	297	11.3	0.253	0.41	0.19
1	150	376	332	14.2	0.206	0.40	0.20
1	185	430	375	17.5	0.164	0.39	0.21
1	240	506	435	22.7	0.125	0.37	0.24
1	300	584	493	28.3	0.100	0.36	0.26
1	400	679	563	37.8	0.0778	0.34	0.29
1	500	786	642	47.2	0.0605	0.33	0.31
1	630	920	734	59.5	0.0469	0.32	0.35

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.