



## 8778 PVC - LSF Alternative Cable



Eland Product Group: A3B

### APPLICATION

8778 Alternative cable is suitable for instrumentation, computer and security applications, point of sale, control systems, and RS232 applications.

### CHARACTERISTICS

**Voltage Rating**  
300V

**Temperature Rating**  
Fixed: -20°C to +80°C

### CONSTRUCTION

**Conductor**  
Class 2 stranded tinned copper

**Insulation**  
PP (Polypropylene)

**Individual Screen**  
Aluminium foil tape

**Drain Wire**  
Stranded tinned copper

**Sheath**  
PVC-LSF (Polyvinyl Chloride-Low Smoke Fume)

### Core Identification

Pair 1: ● Black ● Red  
Pair 2: ● Black ○ White  
Pair 3: ● Black ● Green  
Pair 4: ● Black ● Blue  
Pair 5: ● Black ● Yellow  
Pair 6: ● Black ● Brown

**Sheath Colour**  
● Grey

### THE CABLE LAB®

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



### SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: [www.elandcables.com/company/about-us/esg-sustainability](http://www.elandcables.com/company/about-us/esg-sustainability)



SCIENCE  
BASED  
TARGETS

**BUSINESS  
AMBITION FOR 1.5°C**



### REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab®.





## DIMENSIONS

ELAND PART NO.	NO. OF PAIRS	AWG (NO. OF STRANDS)	NOMINAL DIAMETER OF STRANDS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A3B8778LSFGR	6	AWG22(7)	0.25	8.0	126

## ELECTRICAL CHARACTERISTICS

CAPACITANCE AT 1kHz pF/m	MAXIMUM RESISTANCE OF CONDUCTOR ohms/km
164	49.2